Steering Committee Meeting Agenda – 04/03/2024

1 E 1st St, Reno NV, 89505 – City Hall, 6th Floor Large Conference Room

- 1. Roll Call
- 2. Consent Items (For Consideration):
 - a. 2024 Carryover Amendments
 - i. IBC
 - 1. Section 202 High Rise Buildings Definition
 - 2. Section 305.2 Group E Day Care Facilities
 - 3. Section 308.2 Institutional Group I-1
 - 4. Section 308.5 Institutional Group I-4
 - 5. Section 310.2 Residential Group R-1
 - 6. Section 311.2 Moderate-Hazard Storage Group S-1
 - 7. Section 403.5.4 Smokeproof Enclosures
 - 8. Section 906 Portable Fire Extinguishers
 - 9. Section 910.2 Where required (Smoke and Heat Removal)
 - 10. Section 1210.3.3 Baby Changing Tables
 - 11. Section 1503.6 Snow Shedding and Impact Areas
 - 12. Section 1608.2.1 Ground Snow Loads
 - 13. Section 1609.1.1 Determination of Wind Loads
 - 14. Section 1609.1.1.1 Applicability
 - 15. Section 1609.3 Basic Wind Speeds
 - 16. Section 1704.2 Special Inspections and Tests
 - 17. Section 1803.2 Investigations Required
 - 18. Section 1803.6 Reporting
 - 19. Section 1808.6.1 Foundations
 - 20. Section 1809.5 Frost Protection
 - 21. Section 2901.1 Scope
 - 22. Section 3102.7 Engineering Design
 - 23. Section I105.2 Footings
 - ii. IEBC
 - 1. Section 301 High Rise Buildings
 - 2. Section 301.6 Baby Changing tables
 - iii. IFGC
 - 1. Section 301.1.2 LP-Gas Installations
 - 2. Section 301.16 Snow Hazard

- 3. Section 406.4.1 Test Pressure
- 4. Section 406.4.2 Test Duration
- 5. Section 406.6.2 Before Turning Gas On

iv. IMC

- 1. Section 505.4 Makeup air required
- 2. Section 508.1.4 Evaporative Cooling Systems Used as Makeup Air
- 3. Section 603.2 Duct Sizing

v. UPC

- 1. Chapter 14 Firestop Protection
- 2. Section 216 Definitions
- 3. Section 218 Definition Penetration Firestop System
- 4. Section 222.0 Definitions of "T" Rating
- 5. Section 312.7 Fire-Resistant Construction
- 6. Section 422.0 Minimum Number of Required Fixtures
- 7. Section 609.1 Installation
- 8. Section 712.1 Media
- 9. Section 717.1 General (Size of Building Sewers)
- 10. Section 723.1 General (Building Sewer Test)
- 11.Section 1107.2 Methods of Testing Storm Drainage Systems
- 12. Section 1201.1 Applicability
- 13. Section 1208.6.1.3 Snow Hazard
- 14. Section 1213.3 Test Pressure
- 15. Section 1213.5.1 Turning Gas On

vi. UMC

- 1. Section 304.3 Access to Appliances on Roofs
- 2. Section 403.7.2 Enclosed Parking Garages
- 3. Section 504.4.2.1 Length Limitation
- 4. Section 505.10 Makeup Air
- 5. Section 508.3.5.4 Evaporative Cooling Systems Used as Make Up Air Systems
- 6. Section 511.2.2.2 Capture and Containment Test
- 7. Section 605.1 General
- 8. Section 609.1 Air-Moving Systems and Smoke Detectors
- 9. Section 610.0 Performance Test for Automatic Shutoffs
- 10. Section 939.0 Sauna Heaters

- 11. Section 1301.1 Applicability
- 12. Section 1313.3 Test Pressure
- 13. Section 1313.5.1 Turning Gas On

vii. NEC

- 1. Article 210.52(A)(2) Wall Space
- 2. Article 225.31(B) Locations
- 3. Article 240.51(B) Replacement Only
- 4. Article 250.120 Equipment grounding conductor installation
- 5. Article 358.12 Uses Not Permitted
- 3. New Items (For Consideration):
 - a. New Code Amendments
 - i. IBC
 - 1. Section 2902.1 Required Plumbing Table
 - 2. Section 2902.2 Separate Facilities
 - ii. UPC
 - 1. Section 608.3 Expansion Tanks, and Combination Temperature and Pressure Relief Valves
 - 2. Section 608.5 Discharge Piping
 - iii. NEC
 - 1. Article 358.10(A) Uses Permitted
 - 2. Article 690.7(D) Marking DC PV Circuits
- 4. Next meeting on 5/1/2024 Must attend to vote
- 5. Items to consider for next meeting
- 6. Discussion
- 7. Meeting Adjournment

2024 Carryover Amendment Packet Presented to Steering Committee at 4/3/24 Meeting Steering Committee Vote to take place at 5/1/24 Meeting



Amendment No: Jurisdiction Votes: Y N

Committee: IBC Industry Votes: Y N

Code Section: Section 202 Definitions

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 202 Definitions

Amend Section 202 to read as follows:

HIGH-RISE BUILDING. A building with an occupied floor or occupied roof located more than $\frac{75}{55}$ feet ($\frac{22}{860}$ $\frac{16,764}{100}$ mm) above the lowest level of fire department vehicle access.

International Electrical Code. The Electrical Code, whether the National Electrical Code or the International Electrical Code, as amended and adopted by the local jurisdiction.

International Mechanical Code. The Mechanical Code, whether the Uniform Mechanical Code or the International Mechanical Code as amended and adopted by the local jurisdiction.

International Plumbing Code. The Plumbing Code, whether the Uniform Plumbing Code or the International Plumbing Code, as amended and adopted by the local jurisdiction.

International Fuel Gas Code. The Fuel Gas Code, whether NFPA 54 or the International Fuel Gas Code, as amended and adopted by the local jurisdiction.

Surcharge. A vertical load imposed on the retained soil that may impose a lateral force in addition to the lateral earth pressure of the retained soil. Examples include:

- Sloped retained soil.
- Structure footings supported by the retained soil.
- Adjacent vehicle loads supported by the retained soil.

Supporting statement Indicate if this amendment is:Omission
As adopted by the 2018 NN Amendments. Added "or occupied roof" to High Rise Buildings as stated in 2024 IBC.
Documentation Provide statistics, studies or supporting documents.
See 2018 Amendments and 2024 IBC
Cost analysis State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.
No increase or decrease



Amendment No: J	urisdiction Votes: Y N	1
		•

Committee: IBC Industry Votes: Y N

Code Section: Section 305.2 Group E

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Section 305.2 Group E, day care facilities

Amend Section 305.2 to read as follows:

- 305.2 Group E, day care facilities. This group includes buildings and structures, or portions thereof occupied by more than $\frac{\text{six}}{\text{six}}$ children older than 2 ½ years of age who receive educational, supervision or personal care services for fewer than 24 hours per day.
- **305.2.1 Within Places of religious worship.** Rooms and spaces within *places of religious worship* providing such day care during religious functions shall be classified as part of the primary occupancy.
- 305.2.2 Five Six or fewer children. A facility having five $\underline{\text{six}}$ or fewer children receiving such day care shall be classified as part of the primary occupancy.
- **305.2.3** Five <u>Six</u> or fewer children in a dwelling unit. A facility such as the above within a dwelling unit and having five <u>six</u> or fewer children receiving such day care shall be classified as a Group R-3 occupancy or shall comply with the *International Residential Code*

Supporting statement

Indicate if this amend	lment is:	
Omission	Local environment condition	
_X_Compatibility	Area standard practice	
<u>-</u>	·	

As amended in the 2018 NN Amendments to change 5 to 6 children to be compatible with Nevada State licensing.

Documentation

Provide statistics, studies or supporting documents.

See 2018 Amendments and Nevada State child care licensing requirements.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No increase or decrease.



Amendment No: Jurisdiction Votes: Y N

Committee: IBC Industry Votes: Y N

Code Section: Section 308.2

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Section 308.2 Institutional Group I-1

Amend Section 308.2 to read as follows:

308.2 Institutional Group I-1. Institutional Group I-1 occupancy shall include buildings, structures or portions thereof for more than 16 persons, excluding staff, who reside on a 24-hour basis in a supervised environment and receive custodial care. Buildings of Group I-1 shall be classified as one of the occupancy conditions specified in Section 308.2.1 or 308.2.2. This group shall include, but not be limited to, the following:

Alcohol and drug centers
Assisted living facilities
Congregate care facilities
Group homes
Halfway houses
Residential board and care facilities
Social rehabilitation facilities

- **308.2.1 Condition 1.** This occupancy condition shall include buildings in which all persons receiving custodial care who, without any assistance, are capable of responding to an emergency situation to complete building evacuation.
- **308.2.2 Condition 2.** This occupancy condition shall include buildings in which there are any persons receiving custodial care who require limited verbal or physical assistance while responding to an emergency situation to complete building evacuation.

308.2.3 Six to 16 persons receiving custodial care. A facility housing not fewer than six and not more than 16 persons receiving custodial care shall be classified as Group R-4.

308.2.4 Five or fewer persons receiving custodial care. A facility with five or fewer persons receiving custodial care shall be classified as Group R-3 or shall comply with the International Residential Code provided an automatic sprinkler system is installed in accordance with Section 903.3.1.3 or Section P2904 of the International Residential Code.

308.2.5 Board of Health. All portions of a care facility which houses patients or residents which is classified by the State Board of Health as 'Category 2,' and which has an occupant load of more than 10 residents, is classified as an 'I-1' occupancy classification.

Su	рр	orti	na	sta	tem	ent
	_					

Indicate if this amendr	
Omission	Local environment condition
Compatibility	Area standard practice
As amended by the 20 with the Nevada State	018 NN Amendments. No maintain compatibility Board of health.

Documentation

Provide statistics, studies or supporting documents.

See 2018 Amendments and State Board of Health requirements.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No increase or decrease		



Amendment No: Jurisdiction Votes: Y N

Committee: IBC Industry Votes: Y N

Code Section: Section 308.5

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Section 308.5 Institutional Group I-4, day care facilities Amend Section 308.5 to read as follows:

308.5 Institutional Group I-4, day care facilities. Institutional Group I-4 occupancy shall include buildings and structures occupied by more than five six persons of any age who receive custodial care for fewer than 24 hours per day by persons other than parents or guardians, relatives by blood, marriage or adoption, and in a place other than the home of the person cared for. This group shall include, but not be limited to, the following:

Adult day care Child day care

308.5.1 Classification as Group E. A child day care facility that provides care for more than $\frac{\text{five}}{\text{six}}$ but not more than 100 children 2 ½ years or less of age, where the rooms in which the children are cared for are located on a level of exit discharge serving such rooms and each of these child care rooms has an exit door directly to the exterior, shall be classified as Group E.

308.5.2 Within a place of religious worship. Rooms and spaces within *places of religious worship* providing such care during religious functions shall be classified as part of the primary occupancy.

308.5.3 Five Six or fewer persons receiving care. A facility having five six or fewer persons receiving custodial care shall be classified as part of the primary occupancy.

308.5.4 Five Six or fewer persons receiving care in a dwelling unit. A facility such as the above within a dwelling unit and having five $\underline{\text{six}}$ or fewer persons receiving custodial care shall be classified as a Group R-3 occupancy or shall comply with the International Residential Code.

Supporting statement

As amended in the 2018 NN Amendments to Maintain compatibility with the Nevada State licensing requirements.

Documentation

Provide statistics, studies or supporting documents.

See 2018 NN Amendments and NV State licensing requirements.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No cost increase or decrease



Amendment No:	Jurisdiction Votes: Y	N

Committee: IBC Industry Votes: Y N

Code Section: Section 310.2

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 310.2 Residential Group R-1

Amend Section 310.2 to read as follows:

310.2 Residential Group R-1. Residential Group R-1 occupancies containing *sleeping units* where the occupants are primarily *transient* in nature, including:

Boarding houses (transient) with more than 10 occupants

Brothels

Congregate living facilities (transient) with more than 10 occupants

Hotels (transient)

Motels (transient)

Supporting statement

Indicate if this amendment is:

__Omission __Local environment condition __Compatibility __X_Area standard practice

As amended in the 2018 NN Amendments to include brothels.

Documentation

Provide statistics, studies or supporting documents.

See 2018 NN Amendments.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No increase or decrease in cost.



Amendment No: Jurisdiction Votes: Y N

Committee: IBC Industry Votes: Y N

Code Section: Section 311.2

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

311.2 Moderate-hazard storage, Group S-1. Storage Group S-1 occupancies are buildings occupied for storage uses that are not classified as Group S-2, including, but not limited to, storage of the following:

Aerosol products, Levels 2 and 3

Aircraft hangar (storage and repair)

Bags: cloth, burlap and paper

Bamboos and rattan

Baskets

Belting: canvas and leather

Books and paper in rolls or packs

Boots and shoes

Buttons, including cloth covered, pearl or bone

Cardboard and cardboard boxes Clothing, woolen wearing apparel

Cordage

Beverages over 20% alcohol

Dry boat storage (indoor)

Furniture

Furs

Glues, mucilage, pastes and size

Grains

Horns and combs, other than celluloid

Leather

Linoleum

Lumber

Motor vehicle repair garages complying with the maximum allowable quantities of

hazardous materials listed in Table 307.1(1) (see Section 406.8)

Photo engravings

Resilient flooring
Self-service storage facility (mini-storage)
Silks
Soaps
Sugar
Tires, bulk storage of
Tobacco, cigars, cigarettes and snuff
Upholstery and mattresses
Wax candles

Supporting statement

Indicate if this amenda	nent is:
Omission	Local environment condition
_X_Compatibility	Area standard practice
AS adopted in the 201 include beverages over	18 NN Amendments. IBC added language to er 20% alcohol.

Documentation

Provide statistics, studies or supporting documents.

See 2018 NN Amendments and 2024 IBC	

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No increase or decrease in cost	



Amendment No: Jurisdiction Votes: Y N

Committee: IBC Industry Votes: Y N

Code Section: Section 403.5.4

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 403.5.4 Smokeproof enclosures

Amend Section 403.5.4 to read as follows:

403.5.4 Smokeproof enclosures. Every required interior exit stairway serving floors more than $\frac{75}{55}$ feet ($\frac{22}{860}$ $\frac{16}{764}$ mm) above the lowest level of fire department vehicle access shall be a smokeproof enclosure in accordance with Sections 909.20 and 1023.11

Supporting statement

Indicate if this amend	lment is:
Omission	Local environment condition
X Compatibility	Area standard practice

To maintain compatibility with NV State requirements. See 2018 NN Amendments and NV State requirement.

Documentation

Provide statistics, studies or supporting documents.

See 2018 NN Amendments and NV State requirement.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No cost increase or decrease.	



Amendment No: Jurisdiction Votes: Y	Amendment No:	Jurisdiction Votes:	Y	N
-------------------------------------	---------------	---------------------	---	---

Committee: IBC Industry Votes: Y N

Code Section: Section 906

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 906 Portable Fire Extinguishers

Amend to Section 906 to read as follows:

Refer to the 2024 Editions of the International Fire Code
and the 2024 Northern Nevada Fire Amendments.

Supporting statement

Indicate if this amendme	ent is:
0	1 1

__Omission __Local environment condition

__Compatibility ___Area standard practice

As amended in 2018 NN Amendments to maintain compatibility with the International Fire Code.

Documentation

Provide statistics, studies or supporting documents.

See 2024 NN Ammendments and International Fire Code

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No cost increase or decrease



Amendment No: Jurisdiction Votes: Y N

Committee: IBC Industry Votes: Y N

Code Section: Section 910.2

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 910.2 Where required

Amend Section 910.2 to read as follows:

910.2 Where required. Smoke and heat vents or a mechanical smoke removal system shall be installed as required by Sections 910.2.1 and 910.2.2.

Exceptions:

- 1. Frozen food warehouses used solely for storage of Class I and II commodities where protected by an approved automatic sprinkler system.
- 2. Smoke and heat removal shall not be required in areas of buildings equipped with early suppression fast-response (ESFR) sprinklers. Automatic smoke and heat vents are not required within areas of buildings equipped with early suppression fast-response (ESFR) sprinklers unless the area of Group F-1 or S-1 occupancy protected with the ESFR sprinklers has an exit access travel distance of more than 250 feet (76 200mmn).
- 3. Smoke and heat removal shall not be required in areas of buildings equipped with control mode special application sprinklers with a response time index of 50 (m x S) $^{1/2}$ or less that are listed to control a fire in stored commodities with 12 or fewer sprinklers.

Supporting statement

Indicate if this amendment is: Omission
As amended in the 2018 NN Amendments.
Documentation Provide statistics, studies or supporting documents.
See 2018 NN Amendments
Cost analysis State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.
No cost increase or decrease.



Amendment No:	Jurisdiction Votes: Y	N

Committee: IBC Industry Votes: Y N

Code Section: Section 1210.3.3

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 1210.3.3 Baby Changing Tables

Amend Section 1210.3.3 by adding Section 1210.3.3 as follows:

1210.3.3 Baby Changing Tables. Diaper changing tables are required to be installed in both male, female and other restrooms, in permanent buildings that contain public restrooms as defined in chapter 29 of the 2024 IBC. Changing tables are required when any of the following occur: new buildings, tenant improvements, new restrooms, alteration of existing restrooms, new additions, change of uses that require updating existing restrooms with additions to those facilities. Shall meet the guidelines of 603.5, 309 and 902 of ANSI/ICC A117.1-2017.

Exceptions: A building or facility that does not have public restrooms or has been issued a permit or license which restricts the admission of children on the basis of age, shall be exempt from this requirement.

Supporting statement

Indicate if this amendr		
Omission _X_Compatibility	Local environment condition Area standard practice	

As adopted in the 2018 NN Amendments. To be compatible with NV State NRS 278.584. Changed the numbering to be in accordance with the new section in 2024 IBC. 1210.3.3 is now added after 1210.3.2.

Documentation

Provide statistics, studies or supporting documents.

See NRS 278.584

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No increase or decrease



Amendment No: Jurisdiction Votes: Y N

Committee: IBC Industry Votes: Y N

Code Section: Section 1503.6

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 1503.6 Snow shedding and impact areas

Amend Section 1503 by adding Section 1503.6 as follows:

1503.6 Snow shedding and impact areas. Snow shedding onto adjacent properties is prohibited. Snow shed impact areas shall be designed to contain shedding snow from structures and prevent snow from encroaching onto adjacent properties when ground snow loads exceed 154 p_g when located in Washoe County or Carson City, or exceeds 69 p_g when located in Storey County. The roof and eaves of all structures shall be designed so that snow shed impact areas will not occur in or on required exits, parking areas, driveways, LPG storage tanks, walkways, and public areas.

Exception: The snow shed impact area may be reduced provided an engineered snow restraint system, designed in accordance with this code, is incorporated into the roof design and the roof drainage system.

Supporting statement

Indicate if this amendment is:

__Omission __X_Local environment condition

__Compatibility ___Area standard practice

As amended in the 2018 NN Amendments to reflect local climatic conditions. 1503.6 is now added to IBC after 1503.5

Documentation

Provide statistics, studies or supporting documents.

See 2018 NN Amendments.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No increase or decrease



Amendment No: Jurisdiction Votes: Y N

Committee: IBC Structural Industry Votes: Y N

Code Section: Section 1608.2

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 1608.2 Ground snow loads.

Amend Section 1608.2 to read as follows:

Section 1608.2 Ground snow loads. The ground snow loads for structures shall be determined in accordance with the reliability-targeted (strength based) ground snow load values in Chapter 7 of ASCE & or Figures 1608.2(1) through 1608.2(4) for the contiguous United States and Table 1608.2 for Alaska. Site-specific case studies shall be determined in accordance with Chapter 7 of ASCE 7 and shall be approved by the building official. Snow loads are zero for Hawaii, except in mountainous regions as approved by the building official. The snow loads for elevations above 4500 feet shall be taken from Table 1608.2.1 through 1608.2.4.

Table 1608.2.1 RISK CATEGORY I GROUND SNOW LOADS Pg, FOR NORTHER NEVADA LOCATIONS

Add Table 1608.2.1 to read as follows:

<u>Table 1608.2.1</u>

RISK CATEGORY I GROUND SNOW LOADS, Pg, FOR NORTHERN NEVADA LOCATIONS 2,3

Elevation	West of U.S. 395 , Sierra Slope, Carson City, Reno, Washoe County. West of Highway 88 for Douglas County. ¹	East of U.S. 395 for Carson City, Reno, Sparks, Washoe County. East of Highway 88 for Douglas County. ¹	Lyon County, City of Fernley	Storey County ¹	All Nevada Counties, Lake Tahoe Basin Pg
Feet		Pg (Pounds Per Squ	ıare Foot)		
4500	35	35	12	12	
5000	35	35	35	12	
5100	47	36	36	12	
5200	60	38	36	12	
5300	74	39	39	12	
5400	86	40	40	12	
5500	99	43	43	58	
6000	163	50	50	80	252
6500	196	50	50	103	269
7000	229	66	66	103	286
7500	246	66	66	103	303
8000	262	99	99	103	320
8500	278	99	99	103	338
9000	310	131	131	131	378
9500	343	163	163	138	446
10000	408	163	163	163	480

^{1.} Final roof snow design load Ps or Pf shall not be less than 29 psf

^{2.} Intermediate values may be determined by interpolation

^{3.} Refer to local jurisdiction ordinances for other Ground Snow Loads

Add Table 1608.2.2 to read as follows:

Table 1608.2.1 RISK CATEGORY II GROUND SNOW LOADS Pg, FOR NORTHER NEVADA LOCATIONS

<u>Table 1608.2.2</u>
RISK CATEGORY II GROUND SNOW LOADS, Pg, FOR NORTHERN NEVADA LOCATIONS 1,2

Elevation	West of U.S. 395 , Eastern Sierra Slope, Carson City, Reno, Washoe County, Douglas County and West of Highway 88.	East of U.S. 395 for Carson City, Reno, Sparks, Washoe County, Douglas County and East of Highway 88	Lyon County, City of Fernley	Storey County	All Nevada Counties, Lake Tahoe Basin Western Sierra
Feet		Pg (Pounds Per Squa	re Foot)		Slope
		· · · · · · · · · · · · · · · · · · ·	,		
4500	43	43	15	15	
5000	43	43	43	15	
5100	59	45	45	15	
5200	75	48	45	15	
5300	92	49	49	15	
5400	108	50	50	15	
5500	123	53	53	72	
6000	203	62	62	100	315
6500	245	62	62	129	336
7000	286	82	82	129	358
7500	308	82	82	129	379
8000	328	123	123	129	400
8500	348	123	123	129	422
9000	388	163	163	163	472
9500	429	203	203	172	558
10000	510	203	203	203	600

^{1.} Refer to local jurisdiction ordinances for other Ground Snow Loads

^{2.} Intermediate values may be determined by interpolation

Add Table 1608.2.3 to read as follows:

Table 1608.2.1 RISK CATEGORY III GROUND SNOW LOADS Pg, FOR NORTHER NEVADA LOCATIONS

<u>Table 1608.2.3</u>

RISK CATEGORY III GROUND SNOW LOADS, Pg, FOR NORTHERN NEVADA LOCATIONS 1,2

	SK CATEGORT III GROUND SI	to tr zortboj i gji i ott ito	TTTTETTTT	1 2007 1110110	_
Elevation	West of U.S. 395 , Eastern Sierra Slope, Carson City, Reno, Washoe County, Douglas County and West of State Route 88	East of U.S. 395 for Carson City, Reno, Sparks, Washoe County, Douglas County and East of State Route 88	Lyon County, City of Fernley	Storey County	All Nevada Counties, Lake Tahoe Basin Western Sierra Slope
Feet		Pg (Pounds Per Squ	are Foot)		
4500	48	48	16	16	
5000	48	48	48	16	
5100	65	49	49	16	
5200	82	52	49	16	
5300	101	54	54	16	
5400	118	55	55	16	
5500	136	59	59	79	
6000	224	68	68	110	346
6500	269	68	68	142	370
7000	315	90	90	142	393
7500	338	90	90	142	417
8000	360	136	136	142	440
8500	382	136	136	142	464
9000	426	180	180	180	519
9500	472	224	224	189	613
10000	561	224	224	224	660

^{1.} Refer to local jurisdiction ordinances for other Ground Snow Loads

^{2.} Intermediate values may be determined by interpolation

Add Table 1608.2.4 to read as follows:

Table 1608.2.1 RISK CATEGORY IV GROUND SNOW LOADS Pg, FOR NORTHER NEVADA LOCATIONS

Table 1608.2.4

RISK CATEGORY IV GROUND SNOW LOADS, Pg, FOR NORTHERN NEVADA LOCATIONS 1,2

IXI	SK CATEGORT IV GROUND SI	IOW LOADO, I g, I OK NON	THERM NEVADA	LOCATIONO	· ·
Elevation	West of U.S. 395 , Eastern Sierra Slope, Carson City, Reno, Washoe County, Douglas County and West of State Route 88	East of U.S. 395 for Carson City, Reno, Sparks, Washoe County, Douglas County and East of State Route 88	Lyon County, City of Fernley	Storey County	All Nevada Counties, Lake Tahoe Basin Western Sierra Slope
Feet		Pg (Pounds Per Squa	are Foot)		
4500	52	52	18	18	
5000	52	52	52	18	
5100	71	54	54	18	
5200	90	57	54	18	
5300	110	59	59	18	
5400	129	60	60	18	
5500	148	64	64	86	
6000	244	74	74	120	378
6500	294	74	74	155	403
7000	343	98	98	155	429
7500	369	98	98	155	455
8000	393	148	148	155	480
8500	417	148	148	155	506
9000	465	196	196	196	566
9500	515	244	244	206	669
10000	612	244	244	244	720

^{1.} Refer to local jurisdiction ordinances for other Ground Snow Loads

Supporting statement

^{2.} Intermediate values may be determined by interpolation

As adopted by 2018 NN Amendments. Revised section text to match text in the 2024 IBC.

Documentation

Provide statistics, studies or supporting documents.

Snow Load Memorandum 12/30/23. The loads in this adoption match the previously used loads in the 2018 Northern Nevada Amendments. They have been altered to support the new methodology in the 2024 IBC and ASCE 7-22.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No increase or decrease of cost.



Amendment No: Jurisdiction Votes: Y N

Committee: IBC/IRC Struct Tech Industry Votes: Y N

Code Section: 1609.1.1 Determination of wind loads

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 1609.1.1 Determination of wind loads.

Amend Section 1609.1.1 to read as follows:

1609.1.1 Determination of wind loads. Wind loads on every building or structure shall be determined in accordance with Chapters 26 to 30 of ASCE 7. The type of opening protection required, the basic design wind speed, V, and the exposure category for a site is permitted to be determined in accordance with section 1609 or ASCE 7. The wind speed in the City of Reno, the City of Sparks,

Douglas, Pershing and Washoe Counties shall be per the Special Wind Region Table 1609.3.2. Wind shall be assumed to come from any horizontal direction and wind pressures shall be assumed to act normal to the surface considered.

Exceptions:

- 1. Subject to limitations of section 1609.1.1.1, the provisions of ICC 600 shall be permitted for applicable Group R-2 and R-3 buildings.
- 2. Subject to the limitations of Section 1609.1.1.1, residential *structures* using the provisions of AWC WFCM.
- 3. Subject to the limitations of Section 1609.1.1.1 residential structures using the provisions of AISI S230.
- 4. Designs using NAAMM FP 1001.

- 5. Designs using TIA-222 for antenna-supporting structures and antennas, provided that the horizontal extent of Topographic Category 2 escarpments in Section 2.6.6.2 of TIA-222 shall be 16 times the height of the escarpment.
- 6. Wind tunnel tests in accordance with ASCE 49 and Sections 31.4 and 31.5 of ASCE 7.

The wind speeds in Figures 1609.3(1) through 1609.3(4) are basic design wind speeds, V, and shall be converted in accordance with Section 1609.3.1 to allowable stress design wind speeds, V_{asd} , when the provisions of the standards referenced in Exceptions 4 and 5 are used. The wind speed in the City of Reno, the City of Sparks, Douglas, Pershing and Washoe Counties shall be per the Special Wind Region Table 1609.3.2

Supporting statement

Supporting statement
Indicate if this amendment is:
OmissionLocal environment condition
CompatibilityArea standard practice
As adopted in 2018 NN Amendments. Revised section text to match
text of the 2024 IBC.

Documentation

Provide statistics, studies or supporting documents.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No	increase or	decrease in co	ost.	



Amendment No: Jurisdiction Votes: Y N

Committee: IBC/IRC Struct Tech Industry Votes: Y N

Code Section: 1609.1.1.1 Applicability

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 1609.1.1.1 Applicability.

Amend Section 1609.1.1.1 to read as follows:

1609.1.1.1 Applicability. The provisions of ICC 600 are applicable only to buildings located within Exposure B or C as defined in section 1609.4. The wind speed in the Carson City, City of Reno, the City of Sparks, Douglas, Pershing, Storey, Lyon and Washoe Counties shall be per the Special Wind Region Table 1609.3.2. The provisions of ICC 600, AWC WFCM and AISI S230 shall not apply to buildings sited on the upper half of an isolated hill, ridge, or escarpment meeting all of the following conditions:

- 1. The hill, ridge or escarpment is 60 feet (18288 mm) or higher if located in Exposure B or 30 feet (9144 mm) or higher if located in Exposure C.
- 2. The maximum average slope of the hill exceeds 10 percent.
- 3. The hill, ridge or escarpment is unobstructed upwind by other such topographic features for a distance from the high point of 50 times the height of the hill or 2 miles (3.22 km), whichever is greater.

Supporting statement

Indicate if this amendment is: Omission				
As Adopted by the 2018 NN Amendments.				
Documentation Provide statistics, studies or supporting documents.				
See the 2018 NN Amendments.				
Cost analysis State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.				
No increase or decrease of cost.				



Amendment No: Jurisdiction Votes: Y N

Committee: IBC/IRC Struct Tech Industry Votes: Y N

Code Section: 1609.3 Basic design wind speed

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 1609.3 Basic design wind speed.

Amend Section 1609.3 to read as follows:

1609.3 Basic design wind speed. The basic wind speed, V, in mph, for the determination of the wind loads shall be determined by the Figures 1609.3(1) through 1609.3(4).

The basic wind speed, V, for use in the design of Risk Category I buildings and structures shall be obtained from Figure 1609.3(1).

The basic wind speed, V, for use in the design of Risk Category II buildings and structures shall be obtained from Figure 1609.3(2).

The basic wind speed, V, for use in the design of Risk Category III buildings and structures shall be obtained from Figure 1609.3(3).

The basic wind speed, V, for use in the design of Risk Category IV buildings and structures shall be obtained from Figure 1609.3(4).

Basic wind speed, V, for Hawaii, the US Virgin Islands and Puerto Rico shall be determined by using the ASCE Wind Design Geodatabase. The ASCE Wind Design Geodatabase is available at

https://asce7hazardtool.online, or an approved equivalent.

The basic wind speed, V, for the special wind regions indicated near mountainous terrain and near gorges shall be in accordance with local jurisdiction requirements. The basic wind speeds, V, determined by the local jurisdiction shall be in accordance with Chapter 26 of ASCE 7.

In nonhurricane-prone regions, when the basic wind speed, V, is estimated form the regional climatic data, the basic wind speed, V, shall be determined in accordance with Chapter 26 of ASCE 7.

No altitude density reduction shall be taken.

TABLE 1609.3.2 SPECIAL WIND REGION DEFINED: MINIMUM BASIC WIND SPEEDS

Add Table 1609.3.2 to read as follows:

TABLE 1609.3.2 SPECIAL WIND REGION DEFINED: MINIMUM BASIC WIND SPEEDS

For Carson City, City of Reno, City of Sparks, Douglas,
Lyon, Pershing, Storey and Washoe Counties the design
wind speed values shall be:

Risk Category	Ultimate Wind Speed	V _{asd} Wind Speed
	V _{ult} (mph)	3-sec gust (mph)
I	110	85
II & 2018 IRC	120	93
III	130	101
IV	135	104

Table notes:

a) Air density corrections to design wind pressures are prohibited. The conversions from Vult to Vasd are based on Table 1609.3.1

Supporting statement

mulcate ii tilis ame	enument is:
Omission	X Local environment condition
Compatibility	Area standard practice

As adopted by the 2018 NN Amendments. Revised section text to match text of 2024 IBC.

Documentation

Provide statistics, studies or supporting documents.

See 2018 NN Amendments and 2024 IBC.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No increase or decrease of cost.



Amendment No: Jurisdiction Votes: Y N

Committee: IBC/IRC Struct Tech Industry Votes: Y N

Code Section: 1704.2 Special inspections and tests.

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 1704.2 Special inspections and tests.

Amend Section 1704.2 to read as follows:

1704.2 Special inspections and tests. Where application is made to the building official for construction as specified in Section 105, the owner or the owner's authorized agent, other than the contractor, shall employ one or more approved agencies to provide special inspections and tests during construction on the types of work specified in Section 1705 and identify the approved agencies to the building official. These special inspections and tests are in addition to the inspections by the building official that are identified in Section 110.

Exceptions:

- 1. Special inspections and tests are not required for construction of a minor nature or as warranted by conditions in the jurisdiction as approved by the building official.
- 2. Unless otherwise required by the building official, special inspections and tests are not required for Group R-3 occupancies as applicable in section 101.2 and Group U occupancies that are accessory to a residential occupancy including, but not limited to, those listed in Section 312.1.
- 3. Special inspections and tests are not required for portions of structures designed and constructed in

accordance with the cold-formed steel light-frame construction provisions of Section 2211.1.2 Section 2206.1.2 or the conventional light-frame constructions provisions of Section 2308.

4. The contractor is permitted to employ the approved agencies where the contractor is also the owner.

Supporting statement

Indicate if this amendment is:Omission
As adopted by the 2018 NN Amendments. Revised "Section 221.1.2 to Section 2206.1.2" for compatibility with 2024 IBC.
Documentation Provide statistics, studies or supporting documents.
See 2018 NN Amendments and 2024 IBC.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No increase or decrease in cost.	



Amendment No: Jurisdiction Votes: Y N

Committee: IBC/IRC Struct Tech Industry Votes: Y N

Code Section: 1803.2 Investigations required.

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Section 1803.2 Investigations required.

Amend Section 1803.2 to read as follows:

1803.2 Investigations required. Geotechnical investigations shall be conducted in accordance with Sections 1803.3 through 1803.5. 17

Exception: The building official shall be permitted to waive the requirement for need not require a geotechnical investigation where satisfactory data from adjacent areas is provided by a licensed design professional available that demonstrates an investigation is not necessary for any of the conditions in Sections 1803.5.1 through 1803.5.6 and Sections 1803.5.10 and 1803.5.11.

Supporting statement

Indicate if this amendment is:

__Omission ___Local environment condition

__Compatibility X_Area standard practice

As amended in the 2018 NN Amendments.

Documentation

Provide statistics, studies or supporting documents.

See 2018 NN Amendments

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No increase or decrease in cost.



Amendment No: Jurisdiction Votes: Y N

Committee: IBC/IRC Struct Tech Industry Votes: Y N

Code Section: Section 1803.6 Reporting

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Section 1803.6 Reporting

Amend Section 1803.6 to read as follows:

1803.6 Reporting. Where geotechnical investigations are required, a written report of the investigations shall be submitted to the *building official* by the *permit* applicant at the time of *permit* application. This geotechnical report shall include, but need not be limited to, the following information:

- 1. A plot showing the location of the soil investigations.
- 2. A complete record of the soil boring and penetration test logs and soil samples.
- 3. A record of the soil profile.
- 4. Elevation of the water table, if encountered.
- 5. Recommendations for foundation type and design criteria, including but not limited to: bearing capacity of natural or compacted soil; provisions to mitigate the effects of expansive soils; mitigation of the effects of liquefaction, differential settlement, and varying soil strength; and the effects of adjacent *loads*.
- 6. Expected total and differential settlement.
- 7. Deep foundation information in accordance with Section 1803.5.5.

- 8. Special design and construction provisions for foundations of structures founded on expansive soils, as necessary.
- 9. Compacted fill material properties and testing in accordance with Section 1803.5.8.
- 10. Controlled *low-strength* material properties and testing in accordance with Section 1803.5.9.
- 11. Where required by 1803.5.11, investigation of liquefaction hazards shall be performed in accordance with "Guidelines for Evaluating Liquefaction Hazards in Nevada;" investigation of hazards associated with surface displacement due to faulting or seismically induced lateral spreading or lateral flow shall be performed in accordance with "Guidelines for Evaluating Potential Surface Fault Rupture/Land Subsidence Hazards in Nevada."

Supporting statement

Indicate if this amendment is:

Omission X Local environment condition

__Compatibility __Area standard practice

As amended in the 2018 NN Amendments to reflect local climatic conditions. Added Item 11.

Documentation

Provide statistics, studies or supporting documents.

See 2018 NN Amendments.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No increase or decrease of cost.



Amendment No: Jurisdiction Votes: Y N

Committee: IBC/IRC Struct Tech Industry Votes: Y N

Code Section: 1808.6.1 Foundations

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

1808.6.1 Foundations

Amend Section 1808.6.1 to read as follows:

1808.6.1 Foundations. Foundations placed on or within the active zone of expansive soils shall be designed to resist differential volume changes and to prevent structural damage to the supported structure. Deflection and racking of the supported structure shall be limited to that which will not interfere with the usability and serviceability of the structure.

Foundations placed below where volume change occur or below expansive soil shall comply with the following provisions:

- 1. Foundations extending into or penetrating expansive soils shall be designed to prevent uplift of the supported structure.
- 2. Foundations penetrating expansive soils shall be designed to resist forces exerted on the foundation due to soil volume changes or shall be isolated from the expansive soil.

Post-tensioned slabs shall not be utilized in place of frost depth footing design unless super structure deflection and differential movement calculations are provided. The deflection calculations would need to show that the maximum combined frost and expansive soil heaving, as localized at slab edges, with

resultant non-uniformly distributed deflections, as well as whole slab deflections would not result in super structure racking or excessive truss, roof or wall frame movement.

Suppo	rting	staten	nent
-------	-------	--------	------

Indicate if this amen		
Omission	Local environment condition	
Compatibility	X_Area standard practice	
As amended in the	2018 NN Amendments.	

Documentation

Provide statistics, studies or supporting documents.

See 2018 NN Amendments.	

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No increase or decrease in cost.	



Amendment No: Jurisdiction Votes: Y N

Committee: IBC/IRC Struct Tech Industry Votes: Y N

Code Section: 1809.5 Frost Protection

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Section 1809.5 Frost protection

Amend Section 1809.5(1) to read as follows:

1809.5 Frost protection. Except where otherwise protected from frost, foundations and other permanent supports of buildings and structures shall be protected from frost by one or more of the following methods:

- 1. Extending below the frost line of the locality.

 Refer to 2018 Northern Nevada Amendments Appendix

 Table R301.2(1) for requirements of local Authorities

 Having Jurisdiction.
- 2. Constructing in accordance with ASCE 32.
- 3. Erecting on solid rock.

Exception: Free-standing *buildings* meeting all of the following conditions shall not be required to be protected:

- 1. Assigned to Risk Category I.
- 2. Area of 600 square feet (56 m^2) or less for light-frame construction or 400 square feet (37 m^2) or less for other than light-frame construction.
- 3. Eave height of 10 feet (3048 mm) or less. Shallow foundations shall not bear on frozen soil unless such frozen condition is of a permanent character.

Supporting statement

Indicate if this amendment is:

__Omission X_Local environment condition

CompatibilityArea standard practice
As amended in the 2018 NN Amendments to reflect local climatic conditions.
Documentation
Provide statistics, studies or supporting documents.
See 2018 NN Amendments.
Cost analysis State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.
No increase or decrease of cost.



Amendment No: Jurisdiction Votes: Y N

Committee: IBC Industry Votes: Y N

Code Section: 2901.1 Scope

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 2901.1 Scope

Amend Section 2901.5 to read as follows:

2901.1 Scope. The provisions of this chapter and the International Plumbing Code Uniform Plumbing Code shall govern the design, construction, erection and installation of plumbing components, appliances, equipment and systems used in buildings and structures covered by this code. Toilet and bathing rooms shall be constructed in accordance with Section 1209. Private sewage disposal systems shall conform to the International Private Sewage Disposal Code. The International Fire Code, the International Property Maintenance Code and the International Plumbing Code shall govern the use and maintenance of plumbing components, appliances, equipment and systems. The International Existing Building code and the International Plumbing Code shall govern the alteration, repair, relocation, replacement and addition of plumbing components, appliances, equipment and systems.

Supporting statement

Indicate if this amendment is:

__Omission __Local environment condition

__Compatibility __X_Area standard practice

As adopted in the 2018 Amendments.

Documentation

Provide statistics, studies or supporting documents.

See 2018 Amendments

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No cost increase or decrease



Amendment No:	Jurisdiction Votes: Y	N

Committee: IBC/IRC Struct Tech Industry Votes: Y N

Code Section: 3102.7 Engineering design

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 3102.7 Engineering design.

Amend Section 3102.7 to read as follows:

3102.7 Engineering design. The *structure* shall be designed and constructed to sustain *dead loads; loads* due to tension or inflation; *live loads* including wind, snow or *flood* and seismic loads and in accordance with Chapter 16.

Exception: Membrane structures intended to be in place for 30 days or less may be engineered to risk category I loads provided the installation and use are per the manufacturer's recommendations.

Supporting statement

Indicate if this amend	ment is:
Omission	X Local environment condition
Compatibility	Area standard practice

AS adopted in the 2018 NN Amendments.

DocumentationProvide statistics, studies or supporting documents.

See 2018 NN Amendments.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No increase or decrease in cost.



Amendment No:	Jurisdiction Votes: Y	N

Committee: IBC/IRC Struct Tech Industry Votes: Y N

Code Section: I105.2 Footings

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section I105.2 Footing.

Amend Section I105.2 to read as follows:

I105.2 Footings. In areas with a frost depth of zero, a An unenclosed patio cover that projects 14 feet or less from the main structure shall be permitted to be supported on a concrete slab on grade without footing, provided that the slab conforms to the provisions of Chapter 19 of this code and is not less than 3½ inches (89 mm) thick, and the columns do not support loads in excess of 750 pounds (3.36 kN) per column.

Supporting statement Indicate if this amendment is:

mulcate ii tilis amei	iuiiieiit is.
Omission	Local environment condition
Compatibility	X Area standard practice

Δς	adonted	in	the	2018	NN	Amendments.

Documentation

Provide statistics, studies or supporting documents.

See the 2018 NN Amendments.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No increase or decrease in cost.



Committee: IEBC Industry Votes: Y 0 N 0

Code Section: 902.1

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 902.1 High-rise buildings
Amend Section 902.1 to read as follows:
902.1 High-rise buildings. Any building having occupied floors more than 75 55 feet (22 860 16 764 mm) above the lowest level of fire department vehicle access shall comply with the requirements of Sections 902.1.1 and 902.1.2.

Supporting statement

Indicate if this ame	ndment is:	
Omission	Local environment condition	
Compatibility	_X_Area standard practice	
As required by stat	e law.	
L		

Documentation

Provide statistics, studies or supporting documents.

As required by state law.		

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

As required by state law.	



Amendment No: Jurisdiction Votes: Y 3 N 0

Committee: IEBC Industry Votes: Y 0 N 0

Code Section: 301.6

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Section 301.6 Baby changing tables
Amend Section 301 by adding Section 301.6 to read as follows:

301.6 Baby Changing Tables. Diaper changing tables are required to be installed in both male, female and other restrooms, in permanent buildings that contain public restrooms as defined in chapter 29 of the 2018 IBC. Changing tables are required when any of the following occur: new buildings, tenant improvements, new restrooms, alteration of existing restrooms, new additions, change of uses that require updating existing restrooms with additions to those facilities. Shall meet the guidelines of 603.5, 309 and 902 of ANSI/ICC A117.1-20117.

Exceptions: A building or facility that does not have public restrooms or has been issued a permit or license which restricts the admission of children on the basis of age, shall be exempt from this requirement.

Supporting statement

Indicate if this amend	ment is:	
Omission	Local environment condition	
Compatibility	_X_Area standard practice	
As required by state	law	

Documentation

Provide statistics, studies or supporting documents.

As required by state law

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

As required by state law



Amendment No: Jurisdiction Votes: Y N

Committee: IFGC Industry Votes: Y N

Code Section: 301.1.2

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Add new subsection 301.1.2 to section 301.1:
301.1.2 LP-Gas Installations. Whenever there is a conflict between this code and NFPA 54 and NFPA 58 as adopted by the Nevada LP-Gas Board for LP-Gas installations, the adopted codes of the Nevada LP-Gas Board shall govern.

Supporting statement

Indicate if this amendment is:

__Omission __Local environment condition

_Compatibility ___Area standard practice

As previously adopted in the 2018 Northern Nevada Amendments.

Documentation

Provide statistics, studies or supporting documents.

As previously adopted by the 2018 Northern Nevada Amendments.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No increase or decrease if building costs.



Amendment No: Jurisdiction Votes: Y N

Committee: IFGC Industry Votes: Y N

Code Section: 301.16

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Add new section 301.16 to 301:

301.16 Snow hazard. Protection of utilities shall be per requirements of the local utility.

Supporting statement

Indicate if this amendment is:

__Omission __Local environment condition

_Compatibility ___Area standard practice

As previously adopted in the 2018 Northern Nevada Amendments.

Documentation

Provide statistics, studies or supporting documents.

As previously adopted by the 2018 Northern Nevada Amendments.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No increase or decrease if building costs.



Amendment No: Jurisdiction Votes: <u>Y</u> N

Committee: IFGC Industry Votes: Y N

Code Section: 406.4.1

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Amend section 406.4.1 to read as follows:

406.4.1 Test pressure. The test pressure to be used shall be no less than 1-1/2 times the proposed maximum working pressure, but not less than $\frac{3}{25}$ psig ($\frac{20}{172.4}$ kPa gauge). Where the test pressure exceeds 125 psig (862 kPa gauge), the test pressure shall not exceed a value that produces a hoop stress in the *piping* greater than 50 percent of the specified minimum yield strength of the pipe. This test shall be made before any fixtures or appliances have been attached and before being concealed.

Supporting statement

Indicate if this amendment is:

__Omission ___Local environment condition

__Compatibility ___Area standard practice

As previously adopted in the 2018 Northern Nevada Amendments.

Documentation

Provide statistics, studies or supporting documents.

As previously adopted by the 2018 Northern Nevada Amendments.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No increase or decrease if building costs.



Amendment No: Jurisdiction Votes: Y N

Committee: IFGC Industry Votes: Y N

Code Section: 406.4.2

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Amend section 406.4.2 to read as follows:

406.4.2 Test duration. Test duration shall be not less than 30 minutes. 12 hour for each 500 cubic feet (14 m³) of pipe volume or fraction thereof. When testing a system having a volume less than 10 cubic feet (0.28 m³) or a system in a single family dwelling, the test duration shall be not less than 10 minutes. The duration of the test shall not be required to exceed 24 hours.

Supporting statement

•	1					
1	ndicate	ıt	thic	amand	mant	ıc.
1	Hulcate	ш	นเมอ	annenu	HILEHL	15.

__Omission ___Local environment condition

_Compatibility ___Area standard practice

As previously adopted in the 2018 Northern Nevada Amendments.

Documentation

Provide statistics, studies or supporting documents.

As previously adopted by the 2018 Northern Nevada Amendments.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No increase or decrease if building costs.



Amendment No: Jurisdiction Votes: Y N

Committee: IFGC Industry Votes: Y N

Code Section: 406.6.2

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Section 406.6.2 Before Turning Gas On

Amend Section 406.6.2 to read as follows and add new subsections 405.6.2.1 thru 405.6.2.3:

406.6.2 Before turning gas on. During the process of turning gas on into a system of new gas piping, or portion of a gas system that has been restored after an interruption of service, the entire system shall be inspected to determine that there are no open fittings or ends and that all valves at unused outlets are closed and plugged or capped. In the City of Reno, City of Sparks, Storey County and Washoe County, a manometer test shall be made after all valves, unions, connectors and piping to the appliances complete. A pressure test shall be made with the use of a manometer gauge measuring inches of water column. With all valves including gas cock and gas control valves in the open position, a pressure of at least eleven (11) to fifteen (15) inches of water column shall be measured for at least fifteen (15) minutes with no perceptible drop in pressure.

406.6.2.1 For medium pressure gas systems: Where the appliance is rated for seven (7) to fourteen (14) inches of water column, a manometer test of eleven (11) to fifteen (15) inches of water column will be conducted between the pressure regulating valve and the appliance and the appliance shall be measured for at least fifteen (15) minutes with no perceptible drop in pressure.

406.2.2 For appliances or equipment requiring pounds of gas pressure: A pressure test using a pressure gauge measuring in one tenth (1/10) increments shall be conducted on the gas train of that appliance or equipment. The pressure shall be equal to the appliance's normal operating pressure for a period of thirty (30) minutes with no perceptible drop in pressure.

406.2.3 Manometer testing. Manometer testing shall be performed by a person holding a valid Washoe County manometer tester card for which the number is to be provided at the time of request for inspection. A visual manometer test to be witnessed by the authority having jurisdiction may be allowed by the Building Official. A manometer test does not need to be reported when the serving gas utility performs a manometer or clock test prior to providing service.

Supporting statement Indicate if this amendment is:

mulcate ii tilis amenun	HEHL IS.
Omission	Local environment condition

_Compatibility ___Area standard practice

Adding as previously adopted in the 2018 Northern Nevada Amendments.

Documentation

Provide statistics, studies or supporting documents.

As previously adopted by the 2018 Northern Nevada Amendments.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No added cost.		

Removed the City of Fernley from 406.6.2



Amendment No:	Jurisdiction Votes: Y	N
---------------	-----------------------	---

Committee: IMC Industry Votes: Y N

Code Section: 505.4

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Amend Section 505.4 to read as follows:

505.4 Makeup air required. Exhaust hood systems capable of exhausting in excess of $\frac{400}{600}$ cfm ($\frac{0.19}{0.28}$ m3/s) shall be provided with makeup air at a rate approximately equal to the exhaust air rate. Such makeup air systems shall be equipped with a means of closure and shall be automatically controlled to start and operate simultaneously with the exhaust system

Supporting statement

Indicate if this amend	
Omission	Local environment condition
Compatibility	Area standard practice
As previously adopted	l in the 2018 Northern Nevada Amendments.

Documentation

Provide statistics, studies or supporting documents.

As adopted in the 2018 Northern Nevada Amendments.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No increase or decrease to building costs.



Amendment No: Jurisdiction Votes: Y N

Committee: IMC Industry Votes: Y N

Code Section: 508.1.4

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Add new subsection 508.1.4 to 508.1:

508.1.4 Evaporative Cooling Systems Used as Makeup Air. Evaporative coolers shall not be used for make-up air units on commercial kitchen hoods and kitchen ventilation systems.

Exception: Evaporative cooling systems that are a listed assembly with tempered air for kitchen make-up air systems.

Supporting statement

Inc	licato	it thic	amono	lmont ici
THIC	ııcate	11 11115	annenc	lment is:

__Omission __Local environment condition

_Compatibility ___Area standard practice

As adopted by the 2018 Northern Nevada Amendments.

Documentation

Provide statistics, studies or supporting documents.

As adopted in the 2018 Northern Nevada Amendments.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No increase or decrease in building costs.



Amendment No: Jurisdiction Votes: Y N

Committee: IMC Industry Votes: Y N

Code Section: 603.2

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Amend Section 603.2 to read as follows:

603.2 Duct sizing. Ducts installed within a single dwelling unit shall be sized in accordance with ACCA Manual D based on building loads calculated in accordance with ACCA Manual J or other approved heating and cooling calculations methodologies, the appliance manufacturers installation instructions, or other approved methods. Ducts installed within all other buildings shall be sized in accordance with the ASHRAE Handbook of Fundamentals or other equivalent computation procedure.

Supporting statement

Indicate if this amendment is:

__Omission __Local environment condition

_Compatibility ___Area standard practice

Adding as previously adopted in the 2018 Northern Nevada Amendment.

Documentation

Provide statistics, studies or supporting documents.

As adopted in the 2018 Northern Nevada Amendments.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No increase or decrease to building costs.



Amendment No:	Jurisdiction Votes: Y N									
Committee: UPC	Industry Votes: Y N									
Code Section: Chapter 14										
State proposed amendme Include the entire text of the code portions amended or deleted. <u>Und</u>	e section to be amended. Strike out									
Chapter 14 Firestop Protect:	ion									
Delete Chapter 14 as follow.	s:									
Chapter 14 Firestop Protect: Refer to 2024 International										
	nvironment condition andard practice									
Forwarded from 2018 Amendme	nts.									
Documentation Provide statistics, studies or supp	orting documents.									
See 2018 Amendments										
Cost analysis										

None			



Amendment No:	Jurisdiction Votes:	Y	N
---------------	---------------------	---	---

Committee: UPC Industry Votes: Y N

Code Section: 216.0

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Section 216.0 Definition Non-Combustible Material

Amend Section 216.0 to add as follows:

Section 216.0 Definitions. <u>Mon-Combustible Material:</u>
Materials that, when tested in accordance with

ASTM E136, have at least three of four specimens tested meeting all of the following criteria:

- 1. The recorded temperature of the surface and interior thermocouples shall not at any time during the test rise more than 54°F (30°C) above the furnace temperature at the beginning of the test.
- 2. There shall not be flaming from the specimen after the first 30 seconds.
- 3. If the weight loss of the specimen during testing exceeds 50 percent, the recorded temperature of the surface and interior thermocouples shall not at any time during the test rise above the furnace air temperature at the beginning of the test, and there shall not be flaming of the specimen.

Supporting statement

Indicate if this amendr	
Omission	Local environment condition
_X_Compatibility	Area standard practice
Forwarded from 2018	Amendments.

Documentation

Provide statistics, studies or supporting documents.

See 2018 Amendments

Cost analysis

No Change			



0.000		
Amendment N	lo:	Jurisdiction Votes: Y N
Committee:	UPC	Industry Votes: Y N
Code Section:	218.0	
	ire text of t	the code section to be amended. Strike out ted. Underline added text.
Section 218.	0 Definit	ion Penetration Firestop System
Delete Secti	on 218.0	as follows:
device, which	n has beer led prope of mainta	essembled materials, or a factory-made a tested to a standard test method and, erly on penetrating piping materials, aining the fire-resistance rating of
Supporting : Indicate if this a		
Omission		Local environment condition
_X_Compatibilit		_Area standard practice
Forwarded from	n 2018 Am	nendments.
Documental	tion	
Provide statistic	s, studies	or supporting documents.
See 2018 Ame	ndments	

Cost analysis

None			



Amendment No:	Jurisdiction Votes:	Y	<u> </u>	1
differialiferit No.	Julisuiction votes.			•

Committee: UPC Industry Votes: Y N

Code Section: 222.0

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 222.0 Definitions "T" Rating
Delete Section 222.0 as follows:
222.0 Definitions. T Rating. The time period that the penetration firestop system, including the penetrating item, limits the maximum temperature rise of 325° (181°C) above its initial temperature through the penetration on the non-fire side, where tested in accordance with ASTM E 814 or UL 1479.

Supporting statement

Indicate if this amend	ment is:	
Omission	Local environment condition	
_X_Compatibility	Area standard practice	
Forwarded from 2018	8 Amendments.	

Documentation

Provide statistics, studies or supporting documents.

See	2018	Amendments			

Cost analysis

None			



Amendment No:	Jurisdiction Votes:	Y	N
---------------	---------------------	---	---

Committee: UPC Industry Votes: Y N

Code Section: 312.7

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Section 312.7 Fire-Resistant Construction

Amend Section 312.7 to read as follows:

312.7 Fire-Resistant Construction. Piping penetrations of fire-resistance-rated walls, partitions, floors, floor/ceiling assemblies, roof/ceiling assemblies, or shaft enclosures shall be protected in accordance with the requirements of the building code. and Chapter 14, "Firestop Protection."

Supporting statement

Indicate if this amer	ndment is:	
Omission	Local environment condition	
_X_Compatibility	Area standard practice	
Continued from 20:	18 Northern Nevada Amendments.	

Documentation

Provide statistics, studies or supporting documents.

Continued from 2018 Northern Nevada Amendments.

Cost analysis

None		



es: `	Y	N
	es:	es: <mark>Y</mark>

Committee: UPC Industry Votes: Y N

Code Section: 422.0

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 422.0 Minimum Number of Required Fixtures
Delete Section 422.0 to read: Section 422.0 Minimum Number of Required Fixtures.
Shall comply with 2024 International Building Code Chapter 29.

Supporting statement

indicate if this amendr	nent is:	
Omission	Local environment condition	
_X_Compatibility	Area standard practice	

Forwarded from 2018 Amendments

Documentation

Provide statistics, studies or supporting documents.

	See	2018	Amendmen	ts
--	-----	------	----------	----

Cost analysis

Nana		
None		



Amendment No: Jurisdiction Votes: Y N

Committee: UPC Industry Votes: Y N

Code Section: 609.1

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Section 609.1 Installation

Amend Section 609.1 to read as follows:

609.1 Installation. Water piping shall be adequately supported in accordance with Table 313.3. Burred ends shall be reamed to the full bore of the pipe or tube. Changes in direction shall be made by the appropriate use of fittings, except that changes in direction in copper or copper alloy tubing shall be permitted to be made with bends, provided that such bends are made with bending equipment that does not deform or create a loss in the cross-sectional area of the tubing. Changes in direction are allowed with flexible pipe and tubing without fittings in accordance with the manufacturer's instructions. Provisions shall be made for expansion piping. Piping, hot-water equipment, appurtenances, and devices shall be installed workmanlike manner in accordance with the provisions and intent of the code. Building supply yard piping shall be not less than $\frac{12}{12}$ 6 inches ($\frac{305}{152}$ 152mm) below the average local frost depth. The cover shall be not less than 12 inches (305 mm) below finish grade.

Supporting statement

Indicate if this amendment is:

__Omission __Local environment condition

	C
_X_CompatibilityArea standard practice	
Forwarded from 2018 Amendments	
Documentation	
Provide statistics, studies or supporting documents.	
See 2018 Amendments	
Cost analysis	
State if amendment will increase or decrease building costs. Industry	
member should supply approximate cost (increase or decrease) of	

amendment.



Amendment No: Jurisdiction Votes: Y N

Committee: UPC Industry Votes: Y N

Code Section: 712.1

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 712.1 Media

Amend Section 712.1 to read as follows:

712.1 Media. The piping of the plumbing, drainage and venting systems shall be tested with water or air. except that plastic piping shall not be tested with air. The Authority Having Jurisdiction shall be permitted to require the removal of cleanouts, etc., to ascertain whether the pressure has reached all parts of the system. After the plumbing fixtures have been set and their traps filled with water, they shall be submitted to a final test.

Supporting statement

Indicate if this amendn	nent is:
Omission	Local environment condition
_X_Compatibility	Area standard practice

Forwarded from 2018 Amendments

Documentation

Provide statistics, studies or supporting documents.

See 2018 Amendments

Cost analysis

None		
N1000		
10171114		



Amendment No:	Jurisdiction Votes:	Y	N
---------------	---------------------	---	---

Committee: UPC Industry Votes: Y N

Code Section: 717.1

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 717.1 General (Size of Building Sewers)

Amend Section 717.1 to read as follows:

717.1 General. The minimum size of a building sewer shall be determined on the basis of the total number of fixture units drained by such sewer, in accordance with Table 717.1. No building sewer shall be smaller than the building drain or less than four (4) inches in diameter.

For alternate methods of sizing building sewers, see Appendix ${\tt C.}$

Supporting statement

indicate if this amenum	ient is:
Omission	Local environment condition
_X_Compatibility	Area standard practice

Forwarded	from	2010	1 mana	Imanta
COLWALGEG	11 ()111	7010	AIIICII	111111111

Documentation

Provide statistics, studies or supporting documents.

See 2018 Amendments

Cost analysis

None		



Amendment No: Jurisdiction Votes: Y N

Committee: UPC Industry Votes: Y N

Code Section: 723.1

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 723.1 General (Building Sewer Test)

Amend Section 723.1 to read as follows:

723.1 General. Building sewers shall be tested by plugging the end of the building sewer at its points of connection to the public sewer or private sewage disposal system and completely filling the building sewer with water from the lowest to highest point thereof, or by approved equivalent low-pressure air test. Plastic DWV piping systems shall not be tested by the air test method. The building sewer shall be watertight.

Supporting statement

	dicate if this amendr	nent is:
V Composibility:	Omission	Local environment condition
_X_CompatibilityArea standard practice	_Compatibility	Area standard practice

Forwarded from 2018 Amendments

Documentation

Provide statistics, studies or supporting documents.

See 2018 Amendments

Cost analysis

None		
N1000		
10171114		



Amendment No: Jurisdiction Votes: Y N

Committee: UPC Industry Votes: Y N

Code Section: 1107.2

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 1107.2 Methods of Testing Storm Drainage Systems

Amend Section 1107.2 to read as follows:

1107.2 Methods of Testing Storm Drainage Systems. Except for outside leaders and perforated or open-jointed drain tile, the piping of storm drain systems shall be tested upon completion of the rough piping installation by water or air, except that plastic pipe shall not be tested with air, and proved tight. The Authority Having Jurisdiction shall be permitted to require the removal of cleanout plugs to ascertain whether the pressure has reached parts of the system. One of the following test methods shall be used in accordance with Section 1107.2.1 through Section 1107.2.3.

Supporting statement

Indicate if this amendr	ment is:
Omission	Local environment condition
_X_Compatibility	Area standard practice

Forwarded from 2018 Amendments

Documentation

Provide statistics, studies or supporting documents.

See 2018 Amendments

Cost analysis

None		
NIABA		
13(0))(2)		
INOTIC		



Amendment No: Jurisdiction Votes: Y N

Committee: UPC Industry Votes: Y N

Code Section: 1201.1

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 1201.1 Applicability

Amend Section 1201.1 to read as follows:

1201.1 Applicability. The regulations of this chapter shall govern the installation of fuel gas piping in or in connection with a building, structure or within the property lines of premises up to 5 pounds-force per square inch (psi) (34 kPa) for natural gas and 10 psi (69 kPa) for undiluted propane, other than service pipe. Fuel oil piping systems shall be installed in accordance with NFPA 31. Whenever there is a conflict between this code and NFPA 54 and NFPA 58 as adopted by the Nevada LP-Gas Board for LP-Gas installations, the adopted codes of the Nevada LP-Gas Board shall govern.

Supporting statement

Indicate if this amendn	nent is:
Omission	Local environment condition
_X_Compatibility	Area standard practice

Forwarded from 2018 Amendments and changed installation to applicability.

Documentation

Provide statistics, studies or supporting documents.

See 2018 Amendments

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

None



Amendment No):	Jurisdiction Votes: Y	N
Committee:	UPC	Industry Votes: Y	N
Code Section:	1208.6.1.3		
	e text of the cod	e nt e section to be amended. S derline added text.	Strike out
Section 1208.	6.1.3 Snow Haz	ard	
Add Section 1.	208.6.1.3 to 1	208.6 to read as follow	ws:
	ow Hazard: Pronts of local u	tection of utilities sh tility.	nall be
Supporting sometime in the second sec	nendment is: Local e	environment condition candard practice	
Forwarded from	2018 Amendme	nts.	
Documentati Provide statistics		oorting documents.	
See 2018 Amen	dments		

Cost analysis

None			



Amendment No: Jurisdiction Votes: Y N

Committee: UPC Industry Votes: Y N

Code Section: 1213.3

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 1213.3 Test Pressure

Amend Section 1213.3 to read as follows:

1213.3 Test Pressure. This inspection shall include an air, CO2, or nitrogen pressure test, at which time the gas piping shall stand a pressure of not less than 10 25 psi (69 172.4 kPa) gauge pressure. Test pressures shall be held for a length of time satisfactory to the Authority Having Jurisdiction, but in no case less than $\frac{15}{10}$ 30 minutes with no perceptible drop in pressure. For welded piping, and for piping carrying gas at pressures in excess of 14 inches water column pressure (3.5 kPa), the test pressure shall be not less than 60 psi (414 kPa) and shall be continued for a length of time satisfactory to the Authority Having Jurisdiction, but in no case for less than 30 minutes. For CSST carrying gas at pressures in excess of 14 inches water column (3.5 kPa) pressure, the test pressure shall be not less than 30 psi (207 kPa) for 30 minutes. These tests shall be made using air, CO2, or nitrogen pressure and shall be made in the presence of the Authority Having Jurisdiction. Necessary apparatus for conducting tests shall be furnished by the permit holder. Test gauges used in conducting tests shall be in accordance with Section 318.0.

Supporting statement

Indicate if this amendment is:
OmissionLocal environment condition
CompatibilityArea standard practice
Forwarded from 2018 Amendments.
Documentation
Provide statistics, studies or supporting documents.
Trovide statistics, stadies of supporting accuments.
See 2018 Amendments
Cost analysis
State if amendment will increase or decrease building costs. Industry
member should supply approximate cost (increase or decrease) of
amendment.
Name
None



Amendment No: Jurisdiction Votes: Y N

Committee: IMC, IFGC, UPC, UMC Industry Votes: Y N

Code Section: 24 UPC Section 1213.5.1

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 1213.5.1 Turning Gas On

Amend Section 1213.5.1 to read as follows:

1213.5.1 Turning Gas On. During the process of turning gas on into a system of new gas piping or into a system or portion of a gas system that has been restored after an interruption of service, the entire system shall be inspected to determine that there are no open fittings or ends and that the valves at unused outlets are closed and plugged or capped. [NFPA 54:8.2.2]

1213.5.1.1 During the process of turning gas on into a system of new gas piping or into a system or portion of a gas system that has been restored after an interruption of service; in the City of Reno, City of Sparks, Storey County and Washoe County a manometer test shall be made after all valves, unions, connectors and piping to the appliances are complete. A pressure test shall be made with the use of a manometer gauge measuring inches of water column. With all valves including gas cock and gas control valves in the open position, a pressure of at least eleven (11) to fifteen (15) inches of water column shall be measured for at least fifteen (15) minutes, with no perceptible drop in pressure.

1213.5.1.2 For medium pressure gas systems: Where the appliance is rated for seven (7) to fourteen (14) inches of water column, a manometer test of eleven (11) to fifteen (15) inches of water column will be conducted between the

pressure regulating valve and the appliance and shall be measured for at least fifteen (15) minutes with no perceptible drop in pressure.

1213.5.1.3 For appliances or equipment requiring pounds of gas pressure: A pressure test using a pressure gauge measuring in one tenth (1/10) increments shall be conducted on the gas train of that appliance or equipment. The pressure shall be equal to the appliance's normal operating pressure for a period of thirty (30) minutes with no perceptible drop in pressure.

1213.5.1.4 Manometer testing. Manometer testing shall be performed by a person holding a valid Washoe County manometer tester card in the City of Reno, City of Sparks, Storey County and Washoe County for which the number is to be provided at the time of request for inspection. A visual manometer test to be witnessed by the authority having jurisdiction may be allowed by the Building Official. A manometer test does not need to be reported when the serving gas utility performs a manometer or clock test prior to providing service.

Supporting statement

Indicate if this amen	dment is:
Omission	Local environment condition
_XCompatibility	Area standard practice

Forwarded from 2018 Amendments with the exception of Fernley not requiring a manometer test per 1213.5.1.1 and clarifying which jurisdiction does require a manometer license in section 1213.5.1.4.

Documentation

Provide statistics, studies or supporting documents.

See 2018 Amendments		

Cost analysis

None

Removed City of Fernley from 1213.5.1.1.



Amendment No: Jurisdiction Votes: Y N

Committee: UMC Industry Votes: Y N

Code Section: 304.3

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Section 304.3 Access to Appliances on Roofs

Amend Section 304.3 to read as follows:

Section 304.3 Access to Appliances on Roofs. Appliances located on roofs or other elevated locations above 30 inches shall be accessible. [NFPA 54:9.4.3.1]

304.3.1 Access from the Inside. Buildings of more than 15 feet (4572 mm) in height shall have an inside means of access to the roof unless other means acceptable to the Authority Having Jurisdiction are used [NFPA 54:9.4.3.2]

304.3.1.1 Access Type. The inside means of access shall be a permanent or foldaway inside stairway or ladder, terminating in an enclosure, scuttle, or trapdoor. Such scuttles or trap doors shall be at least 22 inches by 24 inches (559 mm by 610 mm) in size, shall open easily and safely under all conditions, especially snow, and shall be constructed so as to permit access from the roof side unless deliberately locked on the inside.

At least $\frac{6}{10}$ feet ($\frac{1829}{3048}$ mm) of clearance shall be available between the access opening and the edge of the roof or similar hazard, or rigidly fixed rails or guards a minimum of 42 inches (1067 mm) in height shall be provided on the exposed side. Where parapets or other building structures are utilized in lieu of guards or rails, they shall be a minimum of 42 inches (1067 mm) in height. [NFPA 54:9.4.3.3]

Supporting statement
Indicate if this amendment is:
OmissionLocal environment condition
CompatibilityArea standard practice
Adding as previously adopted by the 2018 Northern Nevada Amendments.
Documentation
Provide statistics, studies or supporting documents.
rovide statistics, statics or supporting abcuments.
As previously adopted by the 2018 Northern Nevada Amendments.
Cost analysis
State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.
No increase or decrease in building costs.

Changes made.



Amendment No: Jurisdiction Votes: Y N

Committee: UMC Industry Votes: Y N

Code Section: 403.7.2

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Section 403.7.2 Enclosed Parking Garages

Amend Section 403.7.2 to read as follows:

403.7.2 Enclosed Parking Garages. Mechanical ventilation systems for enclosed parking garages shall operate continuously.

Exceptions:

- (1) Mechanical ventilation systems for enclosed parking garages shall be permitted to operate intermittently where the system is designed to operate automatically upon detection of vehicle operation or presence of occupants by approved automatic detection devices.
- (2) Approved automatic carbon monoxide sensing devices, and nitrogen dioxide detectors shall be permitted to modulate the ventilation system to not exceed a maximum average of 50 parts per million of carbon monoxide, or 1 part per million of nitrogen dioxide during an eight-hour period with a concentration of not more than 200 parts per million for carbon monoxide, or 5 parts per million nitrogen dioxide, for a period not exceeding 15 minutes. Automatic carbon monoxide sensing devices installed in modulated parking garage ventilation systems shall be approved in accordance with Section 301.2.

Supporting statement

Indicate if this amendment is: Omission
Adding as previously adopted by the 2018 Northern Nevada Amendments.
Documentation Provide statistics, studies or supporting documents.
As previously adopted by the 2018 Northern Nevada Amendments.
Cost analysis State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.
No increase or decrease in building costs.



Amendment No: Jurisdiction Votes: Y N

Committee: UMC Industry Votes: Y N

Code Section: 504.4.2.1

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 504.4.2.1 Length Limitation

Amend Section 504.4.2.1 to read as follows:

504.4.2.1 Length Limitation. Unless otherwise permitted or required by the dryer manufacturer's instructions and approved by the Authority Having Jurisdiction, domestic dryer moisture exhaust ducts shall not exceed a total combined horizontal and vertical length of 14 feet (4267 mm), including two 90 degree (1.57 rad) elbows. A length of 2 feet (610 mm) shall be deducted for each 90- degree (1.57 rad) elbow in excess of two.

Exceptions:

Where an exhaust duct power ventilator, in accordance with Section 504.4.2.3, is used, the maximum length of the dryer exhaust duct shall be permitted to be in accordance with the dryer exhaust duct power ventilator manufacturer's installation instructions.

- 1. Where the make and model of the clothes dryer to be installed is known and the manufacture's installation instructions for the clothes dryer are provided to the Authority Having Jurisdiction, the maximum length of the exhaust duct, including any transition duct, shall be permitted to be in accordance with the dryer manufacture's installation instructions.
- 2. Where large-radius 45-degree (0.8 rad) and 90-degree (1.6 rad) bends are installed, determination of the equivalent length of clothes dryer exhaust duct for each bend by engineering calculation in accordance with ASHRAE Fundamentals Handbook shall be permitted.
- 3. <u>Dryer exhaust duct lengths may be increased when justified by calculations prepared</u> and stamped by a Nevada Licensed Mechanical engineer.

Supporting statement Indicate if this amendment is: Omission
Adding as previously adopted by the 2018 Northern Nevada Amendments.
Documentation Provide statistics, studies or supporting documents.
As previously adopted by the 2018 Northern Nevada Amendments.
Cost analysis State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.
No increase or decrease in building costs.



Amendment No:	Jurisdiction Votes:	Y	N
---------------	---------------------	---	---

Committee: UMC **Industry Votes: Y**

Code Section: 505.10

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 505.10 Makeup Air

Amend Section 505.10 to read as follows:

505.10 Makeup Air. Makeup air shall be provided to replenish air exhausted by the ventilation system. Exhaust hood systems capable of exhausting in excess of 600 cfm (0.28 m3/s) shall be provided with makeup air at a rate approximately equal to the exhaust air rate. Such makeup air systems shall be equipped with a means of closure and shall be automatically controlled to start and operate simultaneously with the exhaust system. Makeup air intakes shall be located so as to avoid recirculation of contaminated air within enclosures.

Sunnorting statement

Supporting statement				
Indicate if this amendment is:				
OmissionLocal environr	nent condition			
CompatibilityArea standard	practice			
Adding as previously adopted by the 20 Amendments.	18 Northern Nevada			

Documentation

Provide statistics, studies or supporting documents.

As previously adopted by the 2018 Northern Nevada Amendments.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.



Amendment No:	Jurisdiction Votes:	Y	N
---------------	---------------------	---	---

Committee: UMC Industry Votes: Y N

Code Section: 508.3.5.4

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Section 508.3.5.4 Evaporative Cooling Systems Used as Make Up Air Systems

Add Section 508.3.5.4 to read as follows:

<u>508.3.5.4.1 Evaporative Cooling Systems.</u> Evaporative cooling systems will comply with this chapter. Evaporative coolers shall not be used for makeup air units on commercial kitchen hoods and kitchen ventilation systems.

Exception: Evaporative cooling systems that are part of a listed heating air system for kitchen make up air systems. The temperature differential between the makeup air and the air in the conditioned space shall not exceed 10°F (6°C) except where the added heating and cooling load of makeup air do not exceed the capacity if the HVAC system.

Supporting statement

Indicate if this amendment is:			
	OmissionLocal environment condition		
	CompatibilityArea standard practice		
	Adding as previously adopted by the 2018 Northern Nevada Amendments.		
	7 tillelianienes		

Documentation

Provide statistics, studies or supporting documents.

As previously adopted by the 2018 Northern Nevada Amendments.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.



Amendment No:	Jurisdiction Votes:	Y	N
---------------	---------------------	---	---

Committee: UMC **Industry Votes:** Y

Code Section: 511.2.2.2

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 511.2.2.2 Capture and Containment Test

Amend Section 511.2.2.2 to read as follows:

Section 511.2.2.2 Capture and Containment Test. The permit holder shall verify the capture and containment performance of Type I hoods. A field test shall be conducted with all appliances under the hood at operating temperatures, all the hoods operating at design airflows, and with all sources of replacement air operating at design airflows for the restaurant. Capture and containment shall be verified visually by observing smoke or steam produced by actual cooking operation or by simulating cooking using devices such as smoke candles or smoke puffers. Smoke bombs shall not be used [ASHRAE 154:4.7.2]

Exception: Capture and containment test not required if hood is UL and NFPA listed and manufacturers data lists the individual equipment below hood.

Supporting statement		
Indicate if this amendment is:		
OmissionLocal environment condition		
CompatibilityArea standard practice		
Adding as previously adopted by the 2018 Northern Nevada		
Amendments.		

Documentation

Provide statistics, studies or supporting documents.

As previously adopted by the 2018 Northern Nevada Amendments.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.



Amendment No: Jurisdiction Votes: Y N

Committee: UMC Industry Votes: Y N

Code Section: 605.1 Pending IECC Publication

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Section 605.1 General

Amend Section 605.1 to read as follows:

605.1 General. Air ducts conveying air at temperatures exceeding 140°F (60°C) shall be insulated to maintain an insulation surface temperature of not more than 140°F (60°C). Insulation material on the exterior of ducts shall be legibly printed with the name of the manufacturer, the thermal resistance (R) value at installed thickness, flame-spread index, and smoke developed index of the composite material. Internal duct liners and insulation shall be installed in accordance with SMACNA HVAC Duct Construction Standards – Metal and Flexible.–Supply-air ducts, return air-ducts, and plenum of a heating or cooling system shall be insulated to achieve the minimum thermal (R) value in accordance with the 2018 International Energy Conservation Code Section 403.2.1 for residential and 503.2.7 for commercial.

Exceptions:

- 1. Factory installed plenums, casings, or ductwork furnished as a part of HVAC equipment tested and rated in accordance with approved energy efficiency standards.
- 2. Ducts or plenums located in conditioned spaces where heat gain or heat loss will not increase energy use.
- 3. For runouts less than 10 feet (3048 mm) in length to air terminals or air outlets, the rated R value of insulation need not exceed R 3.5 (R 0.6).
- 4. Backs of air outlets and outlet plenums exposed to unconditioned or indirectly conditioned spaces with face areas exceeding 5 square feet (0.5 m⁻²) need not exceed R-2; those 5 square feet (0.5 m⁻²) or smaller need not be insulated.
- 5. Ducts and plenums used exclusively for evaporative cooling systems.

Supporting statement Indicate if this amendment is: Omission
Adding as previously adopted by the 2018 Northern Nevada Amendments.
Documentation Provide statistics, studies or supporting documents.
As previously adopted by the 2018 Northern Nevada Amendments.
Cost analysis State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.
No increase or decrease in building costs.

Check 2024 IECC and Code Sections.



Amendment No: Jurisdiction Votes: Y N

Committee: UMC Industry Votes: Y N

Code Section: 609.1 (608.1)

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Section 609.1 Air-Moving Systems and Smoke Detectors

Amend Section 609.1 to read as follows:

609.1 Air-Moving Systems and Smoke Detectors. Air-moving systems supplying air in excess of 2000 cubic feet per minute (ft³/min) (0.9439 m³/s) to enclosed spaces within buildings shall be equipped with an automatic shutoff. Automatic shutoff shall be accomplished by interrupting the power source of the air-moving equipment upon detection of smoke in the main supply return-air duct or plenum upstream of any filters, exhaust air connections, outdoor air connections, or decontamination equipment and appliance air duct served by such equipment. Duct smoke detectors shall comply with UL 268A and shall be installed in accordance with NFPA 72 and the manufacturer's installation instructions. Such devices shall be compatible with the operating velocities, pressures, temperatures, and humidities of the system. Where fire-detection or alarm systems are provided for the building, the smoke detectors shall be supervised by such systems in an approved manner.

Supporting statement

Indicate if this amen	dment is:	
Omission	Local environment condition	
Compatibility	Area standard practice	
Adding as previousl	y adopted by the 2018 Northern Nevada	
Amendments.		

Documentation

Provide statistics, studies or supporting documents.

As previously adopted by the 2018 Northern Nevada Amendments.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.



Amendment No: Jurisdiction Votes: Y N

Committee: UMC Industry Votes: Y N

Code Section: 610.0 (609.0)

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Section 610.0 Performance Test for Automatic Shutoffs

Add Section 610.0 to read as follows:

610.0 Performance Test for Automatic Shutoffs. Upon completion and before final approval of the air-moving system, provide with the required smoke detectors, a performance test shall be performed to verify compliance of detector installation to manufacturer's instructions and system compatibility as specified in this chapter. The permittee shall furnish the necessary test equipment and devices required to perform the tests and shall provide the jurisdiction with an accurate, completed, and signed test report. The report shall provide the jurisdiction a form containing equivalent information. At the discretion of the Authority Having Jurisdiction, the performance test may be required to be witnessed by the Authority Having Jurisdiction or performed by an approved third-party testing agency.

Supporting statement

Indicate if this amendment is:
OmissionLocal environment condition
CompatibilityArea standard practice
Adding as previously adopted by the 2018 Northern Nevada Amendments.

Documentation

Provide statistics, studies or supporting documents.

As previously adopted by the 2018 Northern Nevada Amendments.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.



Amendment No: Jurisdiction Votes: Y N

Committee: UMC Industry Votes: Y N

Code Section: 939.0

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 939.0 Sauna Heaters

Amend Section 939.1 to read as follows:

939.1 Electric Sauna Heaters. Sauna heaters shall comply with UL 875 and shall be installed in accordance with the manufacturer's installation instructions. <u>Approved guards or barriers shall be installed to prevent accidental contact with the sauna heater.</u> <u>Ventilation shall be provided in accordance with its listing and combustion air for gasfired sauna heaters shall comply with chapter 7.</u>

Supporting statement

		lment is:

__Omission __Local environment condition

_Compatibility ___Area standard practice

Adding as previously adopted by the 2018 Northern Nevada Amendments.

Documentation

Provide statistics, studies or supporting documents.

As previously adopted by the 2018 Northern Nevada Amendments.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.



Amendment No: Jurisdiction Votes: Y N

Committee: UMC Industry Votes: Y N

Code Section: 1301.1

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Section 1301.1 Applicability

Amend Section 1301.1 to read as follows:

1301.1 Applicability. The regulations of this chapter shall govern the installation of fuel gas piping in or in connection with a building, structure or within the property lines of premises up to 5 pounds-force per square inch (psi) (34 kPa) for natural gas-and 10 psi (69 kPa) for undiluted propane, other than service pipe.

Whenever there is a conflict between this code and NFPA 54 and NFPA 58 as adopted by the Nevada LP-Gas Board for LP-Gas installations, the adopted codes of the Nevada LP-Gas Board shall govern.

Supporting statement

Indicate if this amendment is:			
Omission	Local environment condition		
Compatibility	Area standard practice		
Adding as previously	adopted by the 2018 Northern Nevada		
Amendments.			

Documentation

Provide statistics, studies or supporting documents.

As previously adopted by the 2018 Northern Nevada Amendments.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.



Amendment No: Jurisdiction Votes: Y N

Committee: UMC Industry Votes: Y N

Code Section: 1313.3

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Section 1313.3 Test Pressure

Amend Section 1313.3 to read as follows:

1313.3 Test Pressure. This inspection shall include an air, CO2, or nitrogen pressure test, at which time the gas piping shall stand a pressure of not less than <u>10 25 psi</u> (<u>69 172.4 kPa</u>) gauge pressure. Test pressures shall be held for a length of time satisfactory to the Authority Having Jurisdiction but in no case less than <u>15 30 minutes with no perceptible drop in pressure.</u> For welded piping, and for piping carrying gas at pressures in excess of 14 inches water column (3.5 kPa) pressure, the test pressure shall be not less than 60 psi (414 kPa) and shall be continued for a length of time satisfactory to the Authority Having Jurisdiction, but in no case for less than 30 minutes. For CSST carrying gas at pressures in excess of 14 inches water column (3.5 kPa) pressure, the test pressure shall be 30 psi (207 kPa) for 30 minutes. These tests shall be made using air, CO2, or nitrogen pressure and shall be made in the presence of the Authority Having Jurisdiction. Necessary apparatus for conducting tests shall be furnished by the permit holder. Test gauges used in conducting test shall be in accordance with Section 1303.3.3.1 through Section 1303.3.3.4.

Supporting statement

Indicate if this amend	ment is:	
Omission	Local environment condition	
Compatibility	Area standard practice	
Adding as previously	adopted by the 2018 Northern Nevada	
Amendments.		

Documentation

Provide statistics, studies or supporting documents.

As previously adopted by the 2018 Northern Nevada Amendments.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.



Amendment No: Jurisdiction Votes: Y N

Committee: IMC,IFGC,UPC,UMC Industry Votes: Y N

Code Section: 2024 UMC Section 1313.5.1

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Section 1313.5.1 Turning Gas On

Amend Section 1313.5.1 to read as follows:

1313.5.1 Turning Gas On. During the process of turning gas on into a system of new gas piping or portion of a gas system that has been restored after an interruption of service, the entire system shall be inspected to determine that there are no open fittings or ends and that all valves at unused outlets are closed and plugged or capped. [NFPA 54:8.2.2]

1313.5.1.1 During the process of turning gas on into a system of new gas piping or into a system or portion of a gas system that has been restored after an interruption of service; in the City of Reno, City of Sparks, Storey County and Washoe County a manometer test shall be made after all valves, unions, connectors and piping to the appliances are complete. A pressure test shall be made with the use of a manometer gauge measuring inches of water column. With all valves including gas cock and gas control valves in the open position, a pressure of at least eleven (11) to fifteen (15) inches of water column shall be measured for at least fifteen (15) minutes with no perceptible drop in pressure. 1313.5.1.2 For medium pressure gas systems: Where the appliance is rated for seven (7) to fourteen (14) inches of water column, a manometer test of eleven (11) to fifteen (15) inches of water column will be conducted between the pressure regulating valve and the appliance and shall

measured for at least fifteen (15) minutes with no perceptible drop in pressure.

1313.5.1.3 For appliances or equipment requiring pounds of gas pressure: A pressure test using a pressure gauge measuring in one tenth (1/10) increments shall be conducted on the gas train of that appliance or equipment. The pressure shall be equal to the appliance's normal operating pressure for a period of thirty (30) minutes with no perceptible drop in pressure.

1313.5.1.4 Manometer testing. Manometer testing shall be performed by a person holding a valid Washoe County manometer tester card in the City of Reno, City of Sparks, Storey County and Washoe County for which the number is to be provided at the time of request for inspection. A visual manometer test to be witnessed by the authority having jurisdiction may be allowed by the Building Official. A manometer test does not need to be reported when the serving gas utility performs a manometer or clock test prior to providing service.

Supporting stat	tement
-----------------	--------

Indicate if t	his amendmer:	nt is:
Omission	<u> </u>	Local environment condition
Compatil	oility	_Area standard practice
-	-	
Forwarded	from 2018 An	nendments

Documentation

Provide statistics, studies or supporting documents.

See 2018 Amendments		

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

None	
LINODA	
INOIC	

Note - Also removed City of Fernley.



Amendment No:	Jurisdiction Votes:		N
Committee:	Industry Votes	V	N

Code Section: NEC 210.52(A)(2)

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Amend Article 210.52(A)(2) to read as follows:

- **(2) Wall Space** As used in this section, a wall space shall include the following:
- (1) Any space 600 mm (2 ft) or more in width (including space measured around corners) and unbroken along the floor line by doorways and similar openings, fireplaces, stationary appliances, and fixed cabinets to that do not have countertops or similar work surfaces.
- (2) The space occupied by fixed panels in walls, excluding sliding panels
- (3) The space afforded by fixed room dividers, such as free-standing bar-type counters or railings.

Exceptions:

- (1) The space behind operable doors.
- (2) Vestibules, hallways, and similar areas less than 5ft wide in bedrooms.

Supp	orting statement		
Indica	te if this amendment is	:	
	Omission		Local environment condition
	Compatibility	Χ	Area standard practice

This omits the unusable space behind an operable door as being included in receptacle spacing requirements for dwelling units. This amendment also omits the requirement for receptacles in areas less than 5ft in width from receptacle spacing requirements.

Documentation

Provide statistics, studies or supporting documents.

See 2018 Amendments

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No anticipated cost implications.



Amendment No: Jurisdiction Votes: Y N

Committee: NEC Industry Votes: Y N

Code Section: Article 225.31(B)

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

225.32 225.31(B) Locations

Amend Section 225.32 to read as follows:

225.32 225.31(B) Location. The disconnecting means shall be installed either inside or attached to the outside of the building or structure served or where the conductors pass through the building or structure. The disconnecting means shall be at a readily accessible location nearest the point of entrance of the conductors. For the purposes of this section, the requirements in 203.6 shall be utilized.

Exceptions

- 1. For installations under single management, where documented safe switching procedures are established and maintained for disconnection, and where the installation is monitored by qualified individuals, the disconnecting means shall be permitted to be located elsewhere on the premises.
- 2. For buildings or other structures qualifying under the provisions of Article 685, the disconnecting means shall be permitted to be located elsewhere on the premises.
- 3. For towers or poles used as lighting standards, the disconnecting means shall be permitted to be located elsewhere on the premises.
- 4. For poles or similar structures used only for support of signs installed in accordance with Article 600, the disconnecting means shall be permitted to be located elsewhere on the premises.
- 5. The disconnecting means shall be located independent of the building or structure served, in direct line of sight, but not to exceed thirty feet (30').
- 6. The service disconnecting means may be installed within a building when an external remote shunt trip switch is provided. All shunt trip switches shall be located at seven feet (7') above finish grade at a location approved by the fire department. All shunt trip switches shall be located within a twelve inch (12") equilateral triangle, red in color.

Supporting statement

Indicate if this amendment is: X_OmissionLocal environment conditionCompatibilityArea standard practice
This code section moved.
Documentation Provide statistics, studies or supporting documents.
See 2018 amendments
Cost analysis State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.
No impact.



Amendment No:		Jurisdiction Votes: Y	N
Committee:	NEC	Industry Votes: Y N	
Code Section:	Article 240	0.51(B)	
	text of the c	ment code section to be amended. St <u>Underline</u> added text.	rike out
240.51(B) Replaces only for replacements overfusing or tamperion	1(B) of Section ment Only. Plus in existing institution	on 240.51 Edison-Base Fuses to read Plug fuses of the Edison-base type shall estallations where there is no evidence estisting building where alterations or adviring, all fuse holders shall comply with	ll be used e of <u>Iditions are</u>
Supporting sta Indicate if this ame Omission Compatibility	endment is: Loca	al environment condition a standard practice	
Typographical erro	or		
,	studies or su	upporting documents.	
See 2018 amendr	nents		

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No cost change		



Jurisdiction Votes: V

Amendment No:		Jurisdiction Votes: Y N		
Committee:	NEC	Industry Votes: Y N		
Code Section:	Article 250 13	20		

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

250.120 Equipment Grounding Conductor Installation. An equipment grounding conductor shall be installed in accordance with 250.120(A), (B), and (C) and (D) (D) All raceways installed on roofs shall contain an equipment grounding conductor sized per Table 250.122 installed with the circuit conductors.

Exception: Low voltage, communication and similar type systems unless required elsewhere in the Code.

Supporting	statement
Indicate if this	amendment is:
Omission	Local envir

Local environment condition Compatibility X Area standard practice

The committee is no longer "striking" the verbiage previously stricken, therefore the addition of (D) is now included as previously amended.

Documentation

Provide statistics, studies or supporting documents.

See 2018 Code Amendments		

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

Minimal increase.		



Amendment No: Jurisdiction Votes: Y N

Committee: NEC Industry Votes: Y N

Code Section: NEC 358.12

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

Amend Section 358.12 to read as follows:

358.12 Uses Not Permitted. EMT shall not be used under the following conditions:

- 1. Where subject to severe physical damage
- 2. For the support of luminaires or other equipment except conduit bodies no larger than the largest trade size of the tubing
- 3. In direct contact with earth or direct burial applications

Supporting statement

Indicate if this amendment is	s:	
Omission		Local environment condition
Compatibility	_X_	Area standard practice

EMT is typically made of steel, and prolonged contact with the earth can lead to corrosion over time. Corrosion may compromise the integrity of the conduit, potentially leading to electrical hazards.

The NEC includes requirements for grounding and bonding to ensure electrical systems are properly connected to the earth for safety. Allowing EMT in direct contact with the earth may pose challenges in maintaining proper grounding and bonding.

Alternative materials that may have better corrosion resistance when in contact with the earth, such as PVC conduit, should be used.

Documentation

Provide statistics, studies or supporting documents.

See 2018 Amendments

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

PVC conduit is often considered more cost-effective than EMT for underground applications. PVC is a non-metallic material that is resistant to corrosion, lightweight, and generally less expensive than steel.

2024 New Amendment Packet - 4/3/24 Meeting Presented to Steering Committee at 4/3/24 Meeting Steering Committee Vote to take place at 5/1/24



Amendment No) :	Jurisdiction Votes: Y	N
Committee:	IBC	Industry Votes: Y N	
Code Section:	Section 2902.1	1	
Include the entir		nt e section to be amended. Str erline added text.	ike out
Updated Table 290 See Attached	2.1. Removed section	n referencing section 410 in IPC.	
Supporting s Indicate if this arOmissionCompatibility	mendment is: Local er	nvironment condition andard practice	
not the Internat	•	I the Uniform Plumbing Code ode. We have revised some a n Pluming Code.	
Documentati Provide statistics		orting documents.	
See Uniform Plu	ımbing Code		
	ent will increase of	or decrease building costs. In te cost (increase or decrease	-
None			

- 2			a	a	a	e e	a)	a)	a	a	a	o o	a -	a
	OTHER		1 service sink	1 service sink	1 service sink	1 service sink	1 service sink	1 service sink	1 service sink	1 service sink	1 service sink	1 service sin k°	1 service sink per floor	1 service sink
	PRINKING	(SEE SECTION	1 per 500	1 per 500	1 per 500	1 per 1,000	1 per 500	1 per 1,000	1 per 1,000	1 per 1,000	1 per 1,000	1 per 100	1 per 100	1 per 100
ES	BATHTUBS/	SHOWERS	1	1	1	1	ī	ı	1	Ī	j	ı	ï	1
BING FIXTUR	LAVATORIES	FEMALE	1 per 200	1 per 75	1 per 200	per 250 for the first 750 and 1 per 500 for the remainder exceeding 750	1 per 200	1 per 750	1 per 200	1 per 150	1 per 150	1 per 40 for the first 80 and 1 per 80 for the remain der exceeding 80	1 per 50	1 per 50
JIRED PLUME	LAVAT	MALE	1 per	1 pe	1 per	1 per 250 for the first 750 and 1 per 500 for the remainder exceeding 750	1 per	1 per	1 per	1 per 200	1 per 200	1 per 40 for and 1 per remainder e	1 pe	1 pe
02.1—MINIM UM NUMBER OF REQUI (See Sections 2902.1.1 and 2902.2)	OSETS CTION 424.2)	FEMALE	1 per 65	1 per 40	1 per 75	1 per 50 for the first 400 and 1 per 150 for the remainder exceeding 400	1 per 65	1 per 500	1 per 75	1 per 40 for the first 1,520 and 1 per 60 for the remainder exceeding 1,520	1 per 40 for the first 1,520 and 1 per 60 for the remainder exceeding 1,520	and 1 per 50 for the ceeding 50	1 per 25 for the first 50 and 1 per 50 for the remainder exceeding 50	09
TABLE 2902.1 [P] TABLE 2902.1—MINIMUM NUMBER OF REQUIRED PLUMBING FIXTURES* (See Sections 2902.1.1 and 2902.2.)	WATER CLOSETS (URINALS: SEE SECTION 424.2)	MALE	1 per 125	1 per 40	1 per 75	1 per 100 for the first 400 and 1 per 250 for the remainder exceeding 400	1 per 125	1 per 500	1 per 150	1 per 75 for the first 1,500 and 1 per 120 for the remainder exceeding 1,500	1 per 75 for the first 1,500 and 1 per 120 for the remainder exceeding 1,500	1 per 25 for the first 50 and 1 per 50 for the remainder exceeding 50	1 per 25 for the first 50 and 1 per 50 for the remainder exceeding 50	1 per 50
TABLE 2902.1[P	DESCRIPTION		Theaters and other buildings for the performing arts and motion pictures ^d	Nightclubs, bars, taverns, dance halls and buildings for similar purposes ^d	Restaurants, banquet halls and food courts ^d	Casino gaming areas	Auditoriums without permanent seating, art galleries, exhibition halls, museums, lecture halls, libraries, arcades and gymnasiums ^a	Passenger terminals and transportation facilities ^d	Places of worship and other religious services ^d	Coliseums, arenas, skating rin ks, pools and tennis courts for indoor sporting events and activities!	Stadiums, amusement parks, bleachers and grandstands for outdoor sporting events and activities	Buildings for the transaction of business, nonmedical profes- sional services, other services involving merchandise, office buildings, banks, light indus- trial and similar uses	Ambulatory care facilities and outpatient clinics	Educational facilities
	CLASSIFICATION						Assembly					Business		Educational
	NO.		8				-					2		m

			TABLE 2902.1 [P]		TABLE 2902.1—MINIM UM NUMBER OF REQUIRED PLUMBING FIXTURES* (See Sections 2902.1.1 and 2902.2)—continued	ntinued	SINGFIXIOR	· ·		
Š.	CLASSIFICATION	DESCRIPTION	PTION	WATER CLOSETS (URINALS: SEE SECTION 424.2)	OSETS ECTION 424.2)	LAVATORIES	ORIES	BATHTUBS/	DRINKING	OTHER
				MALE	FEMALE	MALE	FEMALE	SHOWERS	(SEE SECTION	
4	Factory and industrial	Structures in which occupants are engaged in work fabricating, assembly or processing of products or materials	ch occupants ork fabricating, essing of prod-	1 per 100	00:	1 per 100	100	1	1 per 400	1 service sink
		Alcohol and drug centers ^a Congregate care facilities ^b Group homes ^b Halfway houses ^b Social rehabilitation facilities ^b Foster care facilities ^a	centers [®] facilities [®] ion facilities [®] ies [®]	1 per 10 care recipients	recipients	1 per 10 care recipients	0 care ients	1 per 8 care recipients	T	1
			Sleeping units for care recipient	1 per 2 sleeping units	ing units	1 per 2 sleeping units	ping units	1 per 8 sleep- ing units		
		Assisted living and residential board and care facilities with	Dwelling units for care recipients	1 per dwelling unit	ing unit	1 per dwelling unit	lling unit	1 per dwelling unit	1	1 kitchen sink per dwelling unit
2	Institutional	who receive custodial care	Employee facilities	1 per 60 care recipient units	cipient units	1 per 60 care recipient units	0 care nt units	1	1 per 100	1 service sink per floor
		3	Visitor facilities	1 per 75 care recipient units.	ipient units.	1 per 75 care recipient units	5 care nt units	ı	Î	ı
		r	Sleeping units for care recipients	1 per 2 care recipient sleeping units	nt sleeping units	1 per 2 care recipient sleeping units	care eping units	1 per 8 care recipient sleeping units	Ti.	1
		Nursing homes ^b	Employee facilities	1 per 60 care recipient units	cipient units	1 per 60 care recipient sleeping units	0 care eping units	1	1 per 100	1 service sink per floor
			Visitor facilities	1 per 75 care recipient units	cipient units	1 per 75 care recipient sleeping rooms	5 care sleeping ms	1	1	1

		TABLE 2902.1 [F	TABLE 2902.1[P] TABLE 2902.1—MINIMUM NUMBER OF REQURED PLUMBING FIXTURES* (See Sections 2902.1.1 and 2902.2)—continued	UMBER OF REQUING 1902.2)—con	JIRED PLUMBING FIXT	JRES*		3
CLASSIFICATION	DESCRIPTION	PTION	WATER CLOSETS (URINALS: SEE SECTION 424.2)	S N 424.2)	LAVATORIES	BATHTUBS/	PRINKING	OTHER
			MALE	FEMALE	MALE FEMALE	SHOWERS	(SEE SECTION	
		Sleeping units for care recipients	1 per care recipient sleeping unit	ping unit	1 per care recipient sleeping unit	1 per 100 care recipient sleeping units		ī
		Care recipient treatment areas	1 per 25 care recipient treatment rooms	ment rooms	1 per 50 care recipient treatment rooms	1	1 per 100	1
	Hospitals [®]	Employee facilities	1 per 25 care recipient sleeping units or treatment room	1 per 25 care recipient sleeping units or treatment room	1 per 50 care recipient sleeping room or treatment room	11	1 per 100	1service sink per floor
Institutional— continued		Visitor facilities	1 per75 care recipient sleeping units or treatment room	1 per 75 care recipient sleeping units or treatment room	1 per 50 care recipient sleeping room or treatment room	ı	1 per 500	ı
	Prisons ^b		1 per cell		1 per cell	1 per 15	1 per 100	1 service sink
	Reformatories,	Cells	1 per 15		1 per 15	1 per 15	1 per 100	1 service sink
	detention centers and correctional centers ^b	Congregate Living Facilities	1 per 15		1 per 15	1 per 15	1 per 100	1 service sink
		Employees	1 per 25		1 per 35	1	1 per 100	1
	Adult day care and child day care	nd child day	1 per 15		1 per 15	1	1 per 100	1 service sink
Mercantile	Retail stores, service stations, shops, salesrooms, markets and shopping centers	vice stations, ns, markets and s	1 per 500		1 per 750	1	1 per 1,000	1 service sin K°
Docidontial	Hotels, motels, boarding houses (transient)	oardinghouses	1 per dwelling or sleeping unit	ng unit	1 per dwelling or sleeping unit	1 per dwelling or sleeping unit	1	1service sink
	Dormitories, fratemities, sorori- ties and boarding houses (not translent)	emities, sorori- g houses (not	1 per 10		1 per 10	1 per 8	1 per 100	1service sink

3	8		TABLE 2902.1[I	12.1 [P] TABLE 2902.1—MINIMUM NUMBER OF REQUIRED PLUMBING FIXTURES* (See Sections 2902.1.1 and 2902.2)—continued	IUMBER OF REQUand 2902.2)—con	JIRED PLUMBING	G FIXTURE	*S		
NO.	CLASSIFICATION	DESCRIPTION	PTION	WATER CLOSETS (URINALS: SEE SECTION 424.2)	TS NN 424.2)	LAVATORIES	ES	BATHTUBS/	DRINKING	OTHER
				MALE	FEMALE	MALE F	FEMALE	SHOWERS	(SEE SECTION	
			Sleeping units for care recipients	1 per care recipient sleeping unit	eping unit	1 per care recipient sleeping unit	ipient n it	1 per 100 care recipient sleeping units		Ī
			Care recipient treatment areas	1 per 25 care recipient treatment rooms	tmentrooms	1 per 50 care recipient treatment rooms	cipient	1	1 per 100	1
		Hospitals [®]	Employee facilities	1 per 25 care recipient sleeping units or treatment room	1 per 25 care recipient sleeping units or treatment room	1 per 50 care recipient sleeping room or treatment room	ciplent m or oom	1	1 per 100	1service sink per floor
LO.	Institutional—continued		Visitor facilities	1 per 75 care recipient sleeping units or treatment room	1 per 75 care recipient sleeping units or treatment room	1 per 50 care recipient sleeping room or treatment room	cipient m or oom	1	1 per 500	ı
		Prisons ^b		1 per cell	7	1 per cell		1 per 15	1 per 100	1 service sink
		Reformatories,	Cells	1 per 15		1 per 15		1 per 15	1 per 100	1 service sink
		detention centers and correctional centers ^b	Congregate Living Facilities	1 per 15		1 per 15		1 per 15	1 per 100	1 service sink
			Employees	1 per 25		1 per 35		1	1 per 100	1
3		Adult day care and child day care	nd child day	1 per 15		1 per 15		1	1 per 100	1 service sink
9	Mercantile	Retail stores, service stations, shops, salesrooms, markets and shopping centers	vice stations, ns, markets and	1 per 500		1 per 750		1	1 per 1,000	1 service sin k°
1	Recidentia	Hotels, motels, boarding houses (transient)	oardinghouses	1 per dwelling or sleeping unit	oing unit	1 per dwelling or sleeping unit	nit nit	1 per dwelling or sleeping unit	1	1 service sink
		Dormitories, fratemities, sorori- ties and boarding houses (not transient)	emities, sorori- g houses (not	1 per 10		1 per 10		1 per 8	1 per 100	1 service sink



Amendment No: Jurisdiction Votes: Y N

Committee: IBC Industry Votes: Y N

Code Section: Section 2902.2

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

[P] 2902.2 Separate facilities. Where plumbing fixtures are required, separate facilities shall be provided for each sex.

Exceptions:

- 1. Separate toilet facilities shall not be required for *dwelling units* and *sleeping units*.
- 2. Separate toilet facilities shall not be required in structures or tenant spaces with a total *occupant load*, including both employees and customers, of <u>15</u> <u>20</u> or fewer.
- 3. Separate toilet facilities shall not be required in mercantile occupancies in which the maximum *occupant load* is 100 or fewer.
- 4. Separate toilet facilities shall not be required in business occupancies in which the maximum *occupant load* is 25 or fewer.
- 5. Separate toilet facilities shall not be required to be designated by sex where single-user toilet rooms are provided in accordance with Section 2902.1.2.
- 6. Separate toilet facilities shall not be required where rooms having both water closets and lavatory fixtures are designed

for use by all persons regardless of sex and privacy is provided for water closets in accordance with Section 405.3.4 of the International Uniform Plumbing Code and for urinals in accordance with Section 405.3.5 of the *International Uniform Plumbing Code*. **Supporting statement** Indicate if this amendment is: __Local environment condition Omission _x_Compatibility Area standard practice Building Officials in Northern Nevada have noticed a problem with the low occupant loads associated with this section of the code. Especially with A-2 small fast-food restaurants. This amendment would raise the occupant load from 15 to 20 for those type of occupancies. **Documentation** Provide statistics, studies or supporting documents. NA Cost analysis State if amendment will increase or decrease building costs. Industry

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

NA			



Amendment No: Jurisdiction Votes: Y N

Committee: UPC Industry Votes: Y N

Code Section: 608.3

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. Underline added text.

608.3 Expansion Tanks, and Combination Temperature and Pressure Relief Valves.

A water system provided with a check valve, backflow preventer, or other normally closed device that prevents dissipation of building pressure back into the water main, independent of the type of water heater used, shall be provided with an approved, listed, and adequately sized expansion tank or other approved, listed, and adequately sized expansion tank or other approved device having a similar function to control thermal expansion. Pre-pressurized water expansion tanks shall comply with IAPMO/ANSI Z1088. Such expansion tank or other approved device shall be installed on the building side of the check valve, backflow preventer, or other device and shall be sized, securely fastened to the structure and installed in accordance with the manufacturer's installation instructions.

A water system containing storage water heating equipment shall be provided with an approved, listed, adequately sized combination temperature and pressure-relief valve, except for listed nonstorage instantaneous heaters having an inside diameter of not more than 3 inches (80 mm). Each such approved combination temperature and pressure-relief valve shall be installed on the water-heating device in an approved location based on its listing requirements and the manufacturer's installation instructions. Each such combination temperature and pressure-relief valve shall be provided with a drain in accordance with Section 608.5.

Exception: An expansion tank shall not be required for instantaneous non storage water heaters with no internal or external recirculation.

Supporting statement

Indicate if this amen	dment is:
Omission	Local environment condition
Compatibility	Area standard practice

Tankless water heaters with recirculation capabilities need to have an expansion tank. As water is sampled the tankless water heater will fire to maintain loop temperature. This creates thermal expansion until it is dissipated by the opening of a faucet.

Documentation

Provide statistics, studies or supporting documents.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

A small expansion tank, tee, FIP adapter and labor should be less than \$200.00.



Amendment No:	Jurisdiction Votes:	Y	N
---------------	---------------------	---	---

Committee: UPC Industry Votes: Y N

Code Section: 2024 UPC 608.5 (7) & (8)

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Amend sections 608.5 (7) & (8) to read as follows:

- (7) Discharge from a relief valve into a water heater pan shall be prohibited, except if located in a basement with no means of discharge to the outside, no sump pump is available, and a warning device is provided to alert the occupant of water in pan.
- (8) The discharge termination point shall be readily observable, or if unable to terminate outside, is equipped with a warning device for occupant.

Supporting statement

IRC P2804.6.1 (5) allows discharge "to the pan serving the water heater". Although this is not a standard practice, the IRC does allow this in any installation. Area standard when below grade has been to allow the drain to a pan with a warning device.

Documentation

Provide statistics, studies or supporting documents.

N/A		
NI/A		
IN / A		
11//		
,		

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

No cost increase or decrease, this is an alternative to allow water heaters that are being replaced or installed to be brought up to code, and an alternative to have the T & P terminate with a way to notify the occupant if there is a leak, similar to having the "discharge to be readily observable."



Amendment No:	Jurisdiction Votes:	Y	N

Committee: NEC Industry Votes: Y N

Code Section: NEC 358.10(A)

State proposed amendment

Include the entire text of the code section to be amended. Strike out portions amended or deleted. <u>Underline</u> added text.

Amend Section 358.10(A) to read as follows:

358.10 Uses Permitted.

- **(A) Exposed and Concealed.** The use of EMT shall be permitted for both exposed and concealed work for the following:
- (1) In concrete, in direct contact with the earth, in direct burial applications with fittings identified for direct burial, or in areas subject to severe corrosive influences where installed in accordance with 358.10(B)

Supporting statement

Indicate if this amendment is:

____ Omission ____ Local environment condition
___ Compatibility _X Area standard practice

EMT is typically made of steel, and prolonged contact with the earth can lead to corrosion over time. Corrosion may compromise the integrity of the conduit, potentially leading to electrical hazards.

The NEC includes requirements for grounding and bonding to ensure electrical systems are properly connected to the earth for safety.

Allowing EMT in direct contact with the earth may pose challenges in maintaining proper grounding and bonding.

Alternative materials that may have better corrosion resistance when in contact with the earth, such as PVC conduit, should be used.

Documentation

Provide statistics, studies or supporting documents.

Cost analysis

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

PVC conduit is often considered more cost-effective than EMT for underground applications. PVC is a non-metallic material that is resistant to corrosion, lightweight, and generally less expensive than steel.



Cost analysis

NORTHERN NEVADA 2024 CODE AMENDMENT JUSTIFICATION FORM

Amendment No:		Jurisdiction Votes: Y N	
Committee:	NEC	Industry Votes: Y N	
Code Section: NE	C 690.7(D)		
	text of the cod	ent de section to be amended. Strike ou nderline added text.	
ANSI Z535.2-2011 ir	visible <u>etched ph</u> ndicating the high nce with 690.7, s	nenolic or metallic notice label compliant with hest maximum dc voltage in a PV system, shall be provided by the installer at one on	
Supporting sta Indicate if this among Omission Compatibility	endment is: <u>X</u> Local	environment condition standard practice	
"permanent readi	ly visible" and and the enviro	has been debated as what is I in article (110.21) "sufficiently onment involved". This proposal is understandability.	
Documentatio Provide statistics,		porting documents.	

State if amendment will increase or decrease building costs. Industry member should supply approximate cost (increase or decrease) of amendment.

Minimal cost increase.		